




PRODUCT SPECIFICATIONS



PRODUCT NAME

600 & 600B New Masonry Brick Wash Detergent

MANUFACTURER

American Building Restoration Products, Inc.
9720 South 60th Street
Franklin, WI 53132
(414) 421-4125
1-800-346-7532 (Orders Only)
Fax (414) 421-8696
www.abrp.com

PRODUCT DESCRIPTION

600 & 600B New Masonry Brick Wash Detergent are economical cleaners for new masonry installations. They are designed to remove excess grout and clean mortar splatter and staining which occur in new construction. Recommended for use on light colored buff, tan, or pink, glazed brick, tile, stone, exposed aggregate - ideal for all types of masonry construction. **600 & 600B New Masonry Brick Wash Detergent** contain metal inhibitors to control metallic staining. **600 & 600B New Masonry Brick Wash Detergent** will not yellow or bleach natural or colored mortar joints when used in accordance with directions.

600 New Masonry Brick Wash Detergent is used for lightly soiled jobs. **600B New Masonry Brick Wash Detergent** is a concentrate used for heavily soiled jobs.

Limitations: allowing smears and excess mortar or grout to remain on the surface for a long period of time

will result in a more difficult cleaning job which may produce undesirable results. (See **600 Pre-Thickened Efflorescence & Lime Dissolver** instructions.)

Precautions: read the entire Material Safety Data Sheet for a more thorough evaluation of hazards. Protect all surrounding surfaces when using **600 & 600B New Masonry Brick Wash Detergent**. Protect vegetation by covering with tarpaulin. Safety lines and scaffolding must be equipped with steel or acid resistant synthetic ropes. Protect newly painted and aluminum surfaces. Beware of wind drift onto autos and pedestrians. Place snow fence or other barrier to protect project area from pedestrian and/or auto traffic. Block entrance doorways and post warning signs to use other exits. Have cold running water available close by at all times to flush product's liquid if needed to avoid injury or property damage. Do not mix with chlorine type bleaches or other chemicals.

Caution: Avoid contact with hair, skin, eyes, mucous membranes and clothing. Wear protective clothing: use long-sleeved rubber suits, neoprene gloves, chemical splash proof goggles and full face shield. Do not breathe vapor. Use with adequate ventilation. Seek first aid in case of contact or suspicion of contact.

TECHNICAL DATA

Color/Form: amber liquid.

Coverage: approximately 400 sq. ft. per gallon at recommended 4 parts water to 1 part **600 or 600B New Masonry Brick Wash Detergent**. May be diluted up to 12 parts water to 1 part **600B New Masonry Brick Wash Detergent**.

Packaging: one, five and fifty-five gallon containers.

INSTALLATION

Preparatory Work: a test area should be processed on each type of surface before beginning overall cleaning to determine precise procedures necessary. Test recommended strength on small area of building. Allow test areas to dry thoroughly (3-7 days) before determining results. Adjust strength based on tests. User shall determine

the suitability of the product for its intended use and assumes all risk and liability whatsoever in connection therewith.

Note: Cleaning within 2 to 4 weeks of new masonry installation is most effective.

APPLICATION

1. Apply with an acid resistant brush or Plastic Tank Hand Pump Sprayer. Do not use airless or metal sprayers.
2. Dilute **600 or 600B New Masonry Brick Wash Detergent** with water at the ratio determined by dilution tests. Use polyethylene or rubber bucket.
3. Pre-wet a large portion of the masonry surface to be cleaned. When working from staging, keep all lower areas "surface wet" to prevent runoff streaks. Also keep surface rinsed free of cleaning residue.
4. Allow **600 or 600B New Masonry Brick Wash Detergent** to remain on the surface for 2 to 3 minutes. Do not allow **600 or 600B New Masonry Brick Wash Detergent** to dry into masonry which may cause staining. Scrape off excess mortar and reapply **600 or 600B New Masonry Brick Wash Detergent**.
5. Rinse thoroughly with fresh water, brushing the area as the rinse water is applied. For best results use a high pressure water rinse at 400 psi with 4 gallons per minute.

AVAILABILITY

Available through distributors and dealers across the United States and Canada. **NOTICE:** the information and recommendations made herein are based on ABRP, Inc., research and the research of others, and are believed to be accurate. However, no guarantee of their accuracy is made because ABRP, Inc., cannot anticipate every possible application of ABRP, Inc., products, nor anticipate every variation encountered in project surfaces, job conditions, and methods used. For this reason, purchasers shall make their own



American Building Restoration Products, Inc. • Since 1970



PRODUCT SPECIFICATIONS

tests to determine the suitability of such products for a particular purpose. Purchasers assume all risk of use, application and handling of products. Statements concerning the possible use of ABRP, Inc., products are not intended as recommendation to use ABRP, Inc., products in the infringement of any patent.

LIMITED WARRANTY

This warranty is valid for one year from the date of product purchase. Purchaser's claims recovery is limited solely to the following warranty from ABRP, Inc., if the product herein is shown to be defective: ABRP, Inc., at its option, will either replace the product or refund the purchase price. Contact ABRP, Inc., to make claim under this warranty. The purchaser must have proof of purchase from the label and the original sales receipt. Proper surface preparation is essential to the product's performance and is a necessary prerequisite for triggering ABRP, Inc.'s obligation under this warranty. Read and follow label directions and observe all safety precautions in the use of this product. ABRP, Inc., further disclaims, and shall not be liable for, incidental, consequential or indirect damage and/or personal injuries including death arising from the use of this product or the cost of labor involved in its application or any re-application of product that is replaced. SELLER MAKES NO WARRANTY, EXPRESSED OR IMPLIED, CONCERNING THE USE OF THIS PRODUCT OTHER THAN INDICATED ON THE LABEL. BUYER ASSUMES ALL RISK OF USE AND/OR HANDLING OF THIS MATERIAL WHEN SUCH USE AND/OR HANDLING IS CONTRARY TO LABEL INSTRUCTIONS. NO OTHER WARRANTIES ARE MADE, EXPRESSED OR IMPLIED, INCLUDING WITHOUT LIMITATION WARRANTIES AS TO MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. IN ALL EVENTS, ABRP, INC.'S LIABILITY SHALL BE LIMITED SOLELY TO REPLACEMENT OF THE PRODUCT PROVIDED ABOVE. This limited warranty may not be modified or extended by manufacturer's

representatives, distributors or dealers of ABRP, Inc., products. This warranty gives the purchaser specific legal rights, as well as rights which may vary from state to state. ABRP, Inc. specifically disclaims any and all other obligations or liability to any party relative to the sale, use or application of its products.

TECHNICAL SERVICES

ABRP, Inc., employs in-field technical representatives to answer questions for architects, building owners and contractors.

REFERENCING

Catalog, product specifications, brochures, list of national registered historical landmarks restored with ABRP, Inc., products and video training tapes demonstrating a variety of cleaning and restoration projects being performed with ABRP, Inc. products are available upon request. For more information on many of the specialty building restoration products available to you, please see our home page at <http://www.abrp.com> or e-mail ABRP, Inc. at abrp@abrp.com.

Copyright, 2010, American Building Restoration Products, Inc.



American Building Restoration Products, Inc. • Since 1970