




PRODUCT SPECIFICATIONS



PRODUCT NAMES

800 Brush Grade
800 Fast Acting
800 Neutralizer

MANUFACTURER

American Building Restoration Products, Inc.
9720 South 60th Street
Franklin, WI 53132
(414) 421-4125
1-800-346-7532 (Orders Only)
Fax (414) 421-8696
www.abrp.com

PRODUCT DESCRIPTION

800 Paint Strippers are for professional use only. They are lye based (caustic) strippers designed to remove a wide variety of both latex and oil base paint from wood, masonry and metal surfaces. They are specifically formulated to strip multi-layers of organic paint finishes. **800 Paint Strippers** are not designed to strip or dissolve inorganic coatings such as cement, concrete or lime.

800 Paint Strippers do not dry out rapidly on the surface like solvent and methylene chloride paint strippers. They remain wet for longer periods of time allowing for deeper penetration into the paint film without bubbling the finish and are rinsable days after they have dissolved the paint. A longer dwell time will be required when using **800 Paint Strippers** in temperatures below freezing.

800 Brush Grade

800 Brush Grade is a water soluble thick, caustic gel, allowing it to adhere on vertical surfaces. It dissolves multi-layers of oil based finishes in one application. **800 Brush Grade** is more effective if kept damp by misting with water during daytime hours.

800 Fast Acting

800 Fast Acting contains a mixture of lye and alcohol, therefore, a wide variety of paint finishes can be dissolved. **800 Fast Acting** has a gentle affect on wood fiber and grain and is an overall excellent remover of both oil and latex paint. **800 Fast Acting** is also a successful graffiti remover.

800 Neutralizer

800 Neutralizer is the required follow-up to the **800 Paint Strippers** and can be used to neutralize any caustic stripper. **800 Neutralizer** fizzes as it works, taking the guess work out of neutralizing.

Limitations: 800 Paint Strippers will etch plastic, as well as aluminum. Protect these surfaces and all other adjacent surfaces. **800 Paint Strippers** may darken some woods. This darkening can be removed with **X-180 Weathered Wood Restorer™**.

800 Paint Strippers are not recommended for use on veneer, plywood surfaces or other interior woodwork that is to be stained and varnished.

Precautions: read the entire material safety data sheet and product label for a more thorough evaluation of hazards. Fully protect all adjacent surfaces, including any vegetation from coming in direct contact with **800 Paint Strippers**.

Warning: 800 Paint Strippers may cause permanent blindness if splashed into eyes.

TECHNICAL DATA

800 Brush Grade & 800 Fast Acting

Color/Form: dark brown gel.
Coverage: 50 sq. ft. per gallon, depending on layers of paint to strip.
Packaging: one, five and fifty-five gallon containers.

800 Neutralizer

Color/Form: clear liquid
Coverage: 800 sq ft when diluted 1 part **800 Neutralizer** to 3 parts water
Packaging: one, five and fifty-five gallon containers.

INSTALLATION

Preparatory Work: prepare a surface free from dirt and oil. It is not necessary to remove loose, peeling or flaking paint. This creates pockets down to the original masonry or wood surface which is generally more absorbing than the painted surface. Staging should be well maintained and equipped with steel cable. Nylon, cotton or hemp roping is not suitable when using **800 Paint Strippers**.

A test area should be performed prior to beginning overall project to determine optimum dwell time for the product and the number of applications necessary to completely remove all traces of finish from the surface.

User shall determine the suitability of the product for its intended use and assumes all risk and liability whatsoever in connection therewith. Follow all local, state, or federal disposal regulations when using this product.

APPLICATION

1. Apply a thick coat of the **800 Paint Stripper** using a synthetic brush or roller.
2. Let the **800 Paint Stripper** remain on the surface until all paint has dissolved.
3. If the **800 Paint Stripper** remains on the surface in direct sunlight, it may dry prematurely. Rewet the surface by lightly misting with water.

Note: on wood, be certain to remove the **800 Paint Stripper** as soon as the paint has been dissolved. Allowing **800 Paint Strippers** to remain on wood for extended periods of time, may result in raised grain.



American Building Restoration Products, Inc. • Since 1970



PRODUCT SPECIFICATIONS

REMOVAL

To remove the **800 Paint Stripper**, rinse area with a pressure washer. Avoid surface damage by adjusting pressure and nozzle pattern. Once surface has been rinsed it must be neutralized. Apply **800 Neutralizer** any time after stripping is completed. Apply two applications followed by a complete water rinse from a pressure washer. For evidence that **800 Neutralizer** is working, look for a fizzing action. Repeat neutralization process until fizzing stops. Evidence of failing to neutralize properly will cause new paint to discolor in damp weather.

Storage: all **800 Paint Strippers** should be stored in the containers in which they are purchased. **DO NOT** store **800 Paint Strippers** near acids or mix with acid. Doing so could create violent heat reactions.

AVAILABILITY

Available through distributors and dealers across the United States and Canada. **NOTICE:** the information and recommendations made herein are based on ABRP, Inc., research and the research of others, and are believed to be accurate. However, no guarantee of their accuracy is made because ABRP, Inc., cannot anticipate every possible application of ABRP, Inc., products, nor anticipate every variation encountered in project surfaces, job conditions, and methods used. For this reason, purchasers shall make their own tests to determine the suitability of such products for a particular purpose. Purchasers assume all risk of use, application and handling of products. Statements concerning the possible use of ABRP, Inc., products are not intended as recommendation to use ABRP, Inc., products in the infringement of any patent.

LIMITED WARRANTY

This warranty is valid for one year from the date of product purchase. Purchaser's claims recovery is limited solely to the following warranty from ABRP, Inc., if the product herein is shown to be defective: ABRP, Inc., at its option, will

either replace the product or refund the purchase price. Contact ABRP, Inc., to make claim under this warranty. The purchaser must have proof of purchase from the label and the original sales receipt. Proper surface preparation is essential to the product's performance and is a necessary prerequisite for triggering ABRP, Inc.'s obligation under this warranty. Read and follow label directions and observe all safety precautions in the use of this product. ABRP, Inc., further disclaims, and shall not be liable for, incidental, consequential or indirect damage and/or personal injuries including death arising from the use of this product or the cost of labor involved in its application or any re-application of product that is replaced. **SELLER MAKES NO WARRANTY, EXPRESSED OR IMPLIED, CONCERNING THE USE OF THIS PRODUCT OTHER THAN INDICATED ON THE LABEL. BUYER ASSUMES ALL RISK OF USE AND/OR HANDLING OF THIS MATERIAL WHEN SUCH USE AND/OR HANDLING IS CONTRARY TO LABEL INSTRUCTIONS. NO OTHER WARRANTIES ARE MADE, EXPRESSED OR IMPLIED, INCLUDING WITHOUT LIMITATION WARRANTIES AS TO MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. IN ALL EVENTS, ABRP, INC.'S LIABILITY SHALL BE LIMITED SOLELY TO REPLACEMENT OF THE PRODUCT PROVIDED ABOVE.** This limited warranty may not be modified or extended by manufacturer's representatives, distributors or dealers of ABRP, Inc., products. This warranty gives the purchaser specific legal rights, as well as rights which may vary from state to state. ABRP, Inc. specifically disclaims any and all other obligations or liability to any party relative to the sale, use or application of its products.

TECHNICAL SERVICES

ABRP, Inc., employs in-field technical representatives to answer questions for architects, building owners and contractors.

REFERENCING

Catalog, product specifications, brochures, list of national registered historical landmarks restored with ABRP, Inc., products and video training tapes demonstrating a variety of cleaning and restoration projects being performed with ABRP, Inc. products are available upon request. For more information on many of the specialty building restoration products available to you, please see our home page at <http://www.abrp.com> or e-mail ABRP, Inc. at abrp@abrp.com.

Copyright, 2010, American Building Restoration Products, Inc.



American Building Restoration Products, Inc. • Since 1970