

ABR[®]

PRODUCTS, INC.

Restoring, beautifying, preserving wood and stone surfaces.

**Ask about our
certification seminars!**



ABR[®] FAST FINISH REMOVER[™] PRODUCT SPECIFICATIONS

PRODUCT NAME

ABR[®] Fast Finish Remover[™]

MANUFACTURER

American Building Restoration
Products, Inc.
9720 South 60th Street
Franklin, WI 53132
U.S.A.
(414) 421-4125
1-800-346-7532 (Orders Only)
Fax (414) 421-8696
www.abrp.com

PRODUCT DESCRIPTION

Basic Use: **ABR[®] Fast Finish Remover[™]** (for professional use) is an economical, concentrated liquid, water soluble dissolver of stains, latex paints, varnishes, linseed oils and other coatings that hide the original color and texture of wood. Remove prior finishes with **ABR[®] Fast Finish Remover[™]** and start over from the beginning, by restoring wood to the similar condition of new lumber before treating with a new finish. (See **X-100 Natural Seal[®]** products for a new finish). **ABR[®] Fast Finish Remover[™]** removes finishes from all types of surfaces, including masonry and metal. If recoating, neutralize with **X-180 Weathered Wood Restorer[™]**.

Precautions: read the entire material safety data sheet and product label for a more thorough evaluation of hazards. Fully protect all adjacent surfaces including plants and shrubbery. Beware of wind drift onto auto and pedestrian traffic when rinsing or applying **ABR[®] Fast Finish**

Remover[™]. **ABR[®] Fast Finish Remover[™]** should be handled with extreme caution.

Warning: **ABR[®] Fast Finish Remover[™]** may cause permanent blindness if splashed into eyes.

TECHNICAL DATA

Color/Form: brown liquid.

Coverage: 50 to 100 sq. ft. per gallon, depending on layers of paint and finish composition.

Packaging: one, five and fifty-five gallon containers.

INSTALLATION

Preparatory **Work:** it is important to prepare a surface for proper adherence of **ABR[®] Fast Finish Remover[™]**. If dirt or heavy chalk film exists on the surface, rinse with water.

A test area should be performed prior to beginning overall project to determine optimum dwell time for the product to completely penetrate all layers of the finish.

Example: time required for 1 layer of stain or paint may be 30 minutes. Difficult jobs with multiple layers of paint may require leaving **ABR[®] Fast Finish Remover[™]** on test panel for 3 to 4 hours.

User shall determine the suitability of the product for its intended use and assumes all risk and liability whatsoever in connection therewith. Follow all local, state, or federal disposal regulations when using this product.

Application:

1. Dilute 4 parts water to 1 part **ABR[®] Fast Finish Remover[™]**. Do not use full strength. For more difficult jobs use **ABR[®] Strip It-All[™]**.

2. Using a synthetic brush, roller, low pressure sprayer (not to exceed 100 PSI) or a hand pump sprayer (45 PSI) apply a thick coat of **ABR[®] Fast Finish Remover[™]** to surface. Do not use any high pressure airless sprayer.

Caution: **ABR[®] Fast Finish Remover[™]** is slippery when applied to surface. Use extreme caution when working on horizontal surfaces. Do not walk on surfaces coated with **ABR[®] Fast Finish Remover[™]**.

3 Let **ABR[®] Fast Finish Remover[™]** remain on the surface until finish has softened. To prevent premature rinsing, wait for the entire surface to become uniformly darkened. This darkened appearance indicates **ABR[®] Fast Finish Remover[™]** has dissolved the underlying finish and is ready to be rinsed.

4 If **ABR[®] Fast Finish Remover[™]** has to remain on surface for 30 minutes or longer, it may dry prematurely. In this instance, moisten dry areas by applying a 50/50 water/**ABR[®] Fast Finish Remover[™]** mix. Then, mist this surface with a fine water spray. A reapplication may be necessary for overhangs, corners, windows and the like where **ABR[®] Fast Finish Remover[™]** tends to move

downward, therefore, reducing product effectiveness.

Removal:

1. If possible, scrape all dissolved residue and discard in an appropriate container. Follow this procedure with a water rinse (**hot water** works best) ranging from garden hose pressure (which may require scrubbing) to a high pressure water rinse. On **wood**, adjust pressure to 600 psi or lower to avoid damage to wood fiber. Waiting 24 hours to remove **ABR® Fast Finish Remover™** requires more rinse time.

IMPORTANT: the stripping process may darken some woods. This darkening can be removed with a required follow-up wash of **X-180 Weathered Wood Restorer™**

NOTE: for a permanent discoloration in the wood, leave a solution of X-180 **Weathered Wood Restorer™** on the discolored area and allow to dry. A crystallized residue will appear when the **X-180 Weathered Wood Restorer™** dries. Lightly remove crystals from surface without destroying the brightening action of the **X-180 Weathered Wood Restorer™** with a very light water rinse.

2. Certain types of wood surfaces may have a raised grain effect after stripping is completed. Sanding and scraping may be required to smooth out this condition.

Clean Up: water flush equipment, shrubbery, sidewalks, blacktop, asphalt, and other adjacent surfaces immediately upon contact. Leave job site free of any trace amounts of **ABR® Fast Finish Remover™** or dissolved residue. Never leave behind any containers or equipment. Label appropriate containers of residue for disposal.

NOTE: failure to treat wood after cleaning will result in the weathering process to return more rapidly than it originally took to occur at first.

AVAILABILITY

Available through a network of distributors, dealers and representatives established in principal cities across the United States, Canada and Japan.

NOTICE: the information and recommendations made herein are based on **ABRP, Inc.**, research and the research of others, and are believed to be accurate. However, no guarantee of their accuracy is made because **ABRP, Inc.**, cannot anticipate every possible application of **ABRP, Inc.**, products, nor anticipate every variation encountered in project surfaces, job conditions, and methods used. For this reason, purchasers shall make their own tests to determine the suitability of such products for a particular purpose. Purchasers assume all risk of use, application and handling of products. Statements concerning the possible use of **ABRP, Inc.**, products are not intended as recommendation to use **ABRP, Inc.**, products in the infringement of any patent.

LIMITED WARRANTY

This warranty is valid for one year from the date of purchase. The purchaser of this product shall be entitled to the following, if the product herein is shown to be defective: **ABRP, Inc.**, at its option, will either replace the product or refund the purchase price. Contact **ABRP, Inc.**, to make claim under this warranty. The purchaser must have proof of purchase from label and original sales receipt. Proper surface preparation is essential to the applicability of this warranty. Read and follow label directions.

ABRP, Inc., shall not be liable for incidental, consequential or indirect

damage arising from the use of this product or the cost of labor involved in its application.

Seller makes no warranty, expressed or implied, concerning the use of this product other than indicated on the label. Buyer assumes all risk of use and/or handling of this material when such use and/or handling is contrary to label instructions.

No other warranties are made, expressed or implied, including without limitation warranties as to MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

This limited warranty may not be modified or extended by manufacturer's representatives, distributors or dealers of **ABRP, Inc.**, products.

Some states do not allow the exclusion or limitation of incidental or consequential damages so the above limitation or exclusion may not apply to the purchaser. This warranty gives the purchaser specific legal rights, as well as, other rights which may vary from state to state.

TECHNICAL SERVICES

ABRP, Inc., employs in field technical representatives to answer questions for architects, building owners and contractors.

REFERENCING

Catalog, product specifications, brochures, list of national registered historical landmarks restored with **ABRP, Inc.**, products and video training tapes are available upon specific request.

ABRP, INC., is on the **WORLD WIDE WEB**. For more information on many of the specialty building restoration products available to you, please see our home page at <http://www.abrp.com> or e-mail **ABRP, Inc.** at abrp@execpc.com.