

ABR[®]

PRODUCTS, INC.

Restoring, beautifying, preserving wood and stone surfaces.

**Ask about our
certification seminars!**



ABR[®] StripIt-All[™] PRODUCT SPECIFICATIONS

PRODUCT NAME

ABR[®] StripIt-All[™]

MANUFACTURER

American Building Restoration
Products, Inc.

9720 South 60th Street

Franklin, WI 53132

U.S.A.

(414) 421-4125

1-800-346-7532 (Orders Only)

Fax (414) 421-8696

www.abrp.com

PRODUCT DESCRIPTION

Basic Use: **ABR[®] StripIt-All[™]** is a water soluble gel removing multiple layers of latex paints, stains, varnishes, linseed oils and other coatings that hide the original color and texture of wood. **ABR[®] StripIt-All[™]** allows you to start over from the beginning, by restoring wood to the similar condition of new, lumber before treating with a new finish. (See X-100 Natural **Seal[®]** for a finish/ wood preservative). **ABR[®] StripIt-All[™]** removes finishes from all types of surfaces, including masonry and metal.

The **ABR[®] StripIt-All[™]** formula is a replacement to methylene chloride and lye based strippers. Lye based strippers require neutralization and may penetrate into hair line cracks on wood which will interfere with future coatings on the newly stripped surface.

Precautions: read the entire Material Safety Data Sheet and product label for a more thorough evaluation of hazards. Fully protect all adjacent surfaces including plants and

shrubbery. Beware of wind drift onto auto and pedestrian traffic when rinsing or applying **ABR[®] StripIt-All[™]**. Contact local, state or federal agencies to ensure compliance of proper disposal methods and respective regulations.

TECHNICAL DATA

Color/Form: brown semi paste.

Coverage: 75 to 100 sq. ft. per gallon
-1-2 coats of stain.

50 to 75 sq. ft. per gallon -7-2 coats
of latex paint or varnish.

50 sq. ft. per gallon -Combination of
1-3 coats of latex paint and/or oil
paint.

Packaging: one, five and fifty-five
gallon containers.

INSTALLATION

Preparatory Work: it is important to prepare a surface for proper adherence of **ABR[®] StripIt-All[™]**. If dirt or heavy chalk film exists on the surface, rinse with water.

The following procedures are recommendations only, for containment of dissolved residue. These recommendations do not supercede any local, state, or federal disposal regulations:

1. Cover perimeter of building with hay and/or other absorbing material, such as cardboard.
2. To control water run off, place a plastic gutter from the work site area to a designated containment area.
3. To avoid excessive water rinsing, first scrape dissolved paint and then rinse remaining residue with water.

4. Never flush dissolved residue into streams, ponds, lakes or storm sewers.

Note: before beginning overall project, test panels should always be made to determine how much time and which procedure will be required for **ABR[®] StripIt-All[™]** to completely penetrate all layers of the finish.

Example: time required for 1 layer of stain or paint may be 30 minutes. Difficult jobs with multiple layers of paint may require leaving **ABR[®] StripIt-All[™]** on test panel for 3 to 4 hours.

User shall determine the suitability of the product for its intended use and assumes all risk and liability whatsoever in connection therewith.

Application:

1. Using a synthetic brush, roller, low pressure sprayer or airless paint sprayer, apply a thick coat of **ABR[®] StripIt-All[™]** to surface.

Caution: **ABR[®] StripIt-All[™]** is slippery when applied to surface. Use extreme caution when working on horizontal surfaces. Do not walk on surfaces coated with **ABR[®] StripIt-All[™]**.

2. Let **ABR[®] StripIt-All[™]** remain on the surface until all paint or solid color stain has softened. To prevent premature rinsing, wait for the entire surface to become uniformly darkened. This darkened appearance indicates that the **ABR[®] StripIt-All[™]** has dissolved the underlying finish and is ready to be rinsed.

3. If **ABR® StripIt-All™** has to remain on surface for 30 minutes or longer, it may dry prematurely. In this instance, moisten dry areas by applying a 50/50 water/ **ABR® StripIt-All™** mix. Then, mist this surface with a fine water spray. A reapplication may be necessary for overhangs, corners, windows and the like where **ABR® StripIt-All™** tends to move downward and away, therefore reducing, product effectiveness.

Removal:

1. If possible, scrape all dissolved residue and discard in an appropriate container. Follow this procedure with a water rinse (**hot water** works best) ranging from garden hose pressure (which may require scrubbing) to a high pressure water rinse. On **wood**, adjust pressure to 500 psi or lower to avoid damage to wood fiber. Waiting 24 hours to remove **ABR® StripIt-All™** requires more rinse time.

2. **IMPORTANT:** the stripping process may darken some woods. This darkening can be removed with a follow-up wash of **X-180 Weathered Wood Restorer™** after the stripped wood is dry.

NOTE: for a permanent discoloration in the wood, leave a solution of **X-180 Weathered Wood Restorer™** on the discolored area and allow to dry. A crystallized residue will appear when the **X-180 Weathered Wood Restorer™** dries. Lightly remove crystals from surface without destroying the brightening action of the **X-180 Weathered Wood Restorer™** with a very light water rinse.

3. Certain types of wood surfaces may have a raised grain effect after stripping is completed. Sanding and scraping may be required to smooth out this condition.

Clean Up: water flush equipment, shrubbery, sidewalks, blacktop, asphalt, and other adjacent surfaces immediately upon contact. Leave job site free of any trace amounts of **ABR® StripIt-All™** or dissolved residue. Never leave behind any containers or equipment. Label appropriate containers of residue for disposal.

PRESERVING THE WOOD SURFACE WITH X-100 NATURAL SEAL@

Follow the complete wood restoration

process with the application of **X-100 Natural Seal@ Wood Preservative**. **X-100 Natural Seal@** formula is a wood preservative consisting of essential wood protecting ingredients blended in a paraffinic oil which is non-sensitive to ultra violet rays. Application of **X-100 Natural Seal@** prevents future stripping. **X-100 Natural Seal@** is not a varnish or film forming coating. Film forming coatings can peel and may need to be stripped, sanded or scraped when reapplication is necessary.

Independent scientific tests by forest service laboratories have proven **X-100 Natural Seal@** to be technologically superior in maintaining the wood's natural color with outstanding water repellency.

NOTE: failure to treat wood after cleaning will result in the weathering process to return more rapidly than it originally took to occur at first.

AVAILABILITY

Available through a network of distributors, representatives and dealers established in principal cities across the United States, Canada, and Japan.

Notice: the information and recommendations made herein are based on **ABRP Inc.**, research and the research of others, and are believed to be accurate. However, no guarantee of their accuracy is made because **ABRP Inc.**, cannot anticipate every possible application of **ABRP Inc.**, products, nor anticipate every variation encountered in project surfaces, job conditions and methods used. For this reason, purchasers shall make their own tests to determine the suitability of such products for a particular purpose. Purchasers assume all risk of use, application and handling of products. Statements concerning the possible use of **ABRP Inc.**, products are not intended as recommendation to use **ABRP Inc.**, products in the infringement of any patent.

LIMITED WARRANTY

This warranty is valid for one year from the date of purchase. The purchaser of this product shall be entitled to the following, if the product herein is shown to be defective: **ABRP, Inc.**, at its option, will either replace the product or refund the purchase price. Contact **ABRP, Inc.**, to make a claim under this warranty.

The purchaser must have proof of purchase from label and original sales receipt. Proper surface preparation is essential to the applicability of this warranty. Read and follow label directions.

ABRP, Inc., shall not be liable for incidental, consequential or indirect damage arising from the use of this product or the cost of labor involved in its application.

Seller makes no warranty, expressed or implied, concerning the use of this product other than indicated on the label. Buyer assumes all risk of use and/or handling of this material when such use and/or handling is contrary to label instructions.

No other warranties are made, expressed or implied, including without limitation warranties as to MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

This limited warranty may not be modified or extended by manufacturer's representatives, distributors or dealers of **ABRP, Inc.**, products.

Some states do not allow the exclusion or limitation of incidental or consequential damages so the above limitation or exclusion may not apply to the purchaser. This warranty gives the purchaser specific legal rights, as well as, other rights which may vary from state to state.

TECHNICAL SERVICES

ABRP, Inc., employs in field technical representatives to answer questions for architects, building owners and contractors.

REFERENCING

Catalog, product specifications, brochures, list of nationally registered historical landmarks restored with **ABRP, Inc.**, products and video training tapes are available upon specific request.

ABRP, INC., is on the **WORLD WIDE WEB**. For more information on many of the specialty building restoration products available to you, please see our home page at <http://www.abrp.com> or e-mail **ABRP, Inc.** at abrp@execpc.com.

©Copyright, 2000, American Building Restoration Products, Inc.