




PRODUCT SPECIFICATIONS



PRODUCT NAME 800 FAST ACTING GRIP 'N STRIP®

MANUFACTURER

American Building Restoration
Products, Inc.
9720 South 60th Street
Franklin, WI 53132
U.S.A.
(414) 421-4125
1-800-346-7532 (Orders Only)
Fax (414) 421-8696
www.abrp.com

PRODUCT DESCRIPTION

Basic Use: 800 FAST ACTING GRIP 'N STRIP® peel and scrape off paste paint remover is an effective way to remove multiple layers of lead-based oils, latex paints, varnishes, stains and other finishes in one application on wood, masonry, plastered walls or metals.

800 FAST ACTING GRIP 'N STRIP® paint remover is designed to produce its own outer skin, making it easy to use requiring no paper over lay.

The 800 FAST ACTING GRIP 'N STRIP® formula is an ideal paint remover for intricate carvings, moldings, pillars, capitals, overhangs, ceilings and where normal removers do not adequately penetrate. With its paste like consistency applied uniformly, 800 FAST ACTING GRIP 'N STRIP®

penetrates more layers of paint mil thickness and reduces water rinse normally needed to dissolve stripper residue. 800 FAST ACTING GRIP 'N STRIP® clings to vertical and overhang surfaces preventing sagging, dripping and sliding. 800 FAST ACTING GRIP 'N STRIP® is available in a wide range of formulas. This variety is to protect surfaces against excess damage that can be caused by strong caustics. 800 FAST ACTING GRIP 'N STRIP® is a caustic paint remover that requires neutralization (See 800 Neutralizer label and product specification sheet.) 800 FAST ACTING GRIP 'N STRIP® is not recommended for use on veneered or plywood surfaces, or when preparing wood cabinets or other interior woodwork for a stained and varnished finish. (Acceptable only if surface is just to be painted). 800 FAST ACTING GRIP 'N STRIP® will etch lexan, and other common protective plastic, as well as aluminum. Protect these surfaces. 800 FAST ACTING GRIP 'N STRIP® should be handled with extreme caution.

Limitations: 800 FAST ACTING GRIP 'N STRIP® may darken the woods surface. This darkening can be removed with X-180 Weathered Wood Restorer™.

Precautions: read the entire material safety data sheet and product label for a more thorough evaluation of hazards. Fully protect all adjacent surfaces, including vegetation and aluminum from coming in direct contact with 800 FAST ACTING GRIP 'N STRIP®. When stripping interiors, lay plastic sheeting on floor then cover plastic with stacks of newspaper or cardboard to absorb scraped residue.

TECHNICAL DATA

Color/Form: tan paste.

Coverage: 25 to 50 sq. ft. per gallon , depending on layers of paint to strip.

Packaging: one and five gallon containers.

INSTALLATION

Preparatory Work: prepare a surface free from dirt and oil. It is not necessary to remove loose, peeling or flaking paint. This creates pockets down to the original masonry or wood surface which is generally more absorbing than the painted surface.

A test area should be performed prior to beginning overall project to determine optimum dwell time for the product and the number of applications necessary to completely remove all traces of finish from the surface.

User shall determine the suitability of the product for its intended use and assumes all risk and liability whatsoever in connection therewith. Follow all local, state, or federal disposal regulations when using this product.

Application:

1. Apply 800 FAST ACTING GRIP 'N STRIP® approximately 1/8-1/4 inch thick with a trowel, or synthetic brush.

2. Allow 800 FAST ACTING GRIP 'N STRIP® to remain on surface until all paint is dissolved. 1 to 24 hours may be required. 800 FAST ACTING GRIP 'N STRIP® will penetrate an average of one (1) layer of paint per hour.

CAUTION: allowing 800 FAST ACTING GRIP 'N STRIP® to remain on wood for extended periods of time, may result in raised grain.

3. Covering 800 FAST ACTING GRIP 'N STRIP® with plastic sheeting may increase product effectiveness. Although it is not required, test to determine if covering is beneficial. Product efficiency is slower in cooler temperatures.

Removal:

1. Scrape and peel off formed membrane. Rinse with water to completely remove 800 FAST ACTING GRIP 'N STRIP® residue. Beware of wind drift onto adjacent surfaces.

2. When using 800 FAST ACTING GRIP 'N STRIP®, neutralize the surface with ABRP 800 Neutralizer. Rinse 800 Neutralizer. (Read label for all instructions).

Storage: 800 FAST ACTING GRIP 'N STRIP® should be stored in the containers in which they are purchased. Avoid storing 800 FAST





PRODUCT SPECIFICATIONS

ACTING GRIP 'N STRIP® near acids or mixing with acid. Failure to do so could create violent heat reactions.

AVAILABILITY

Available through a network of distributors, dealers and representatives established in principal cities across the United States, Canada and Japan.

NOTICE: the information and recommendations made herein are based on ABRP, Inc., research and the research of others, and are believed to be accurate. However, no guarantee of their accuracy is made because ABRP, Inc., cannot anticipate every possible application of ABRP, Inc., products, nor anticipate every variation encountered in project surfaces, job conditions, and methods used. For this reason, purchasers shall make their own tests to determine the suitability of such products for a particular purpose. Purchasers assume all risk of use, application and handling of products. Statements concerning the possible use of ABRP, Inc., products are not intended as recommendation to use ABRP, Inc., products in the infringement of any patent.

LIMITED WARRANTY

This warranty is valid for one year from the date of product purchase. Purchaser's claims recovery is limited solely to the following warranty from ABRP, Inc., if the product herein is shown to be defective: ABRP, Inc., at its option, will either replace the product or refund the purchase price. Contact ABRP, Inc., to make claim under this warranty. The purchaser must have proof of purchase from the

label and the original sales receipt. Proper surface preparation is essential to the product's performance and is a necessary prerequisite for triggering ABRP, Inc.'s obligation under this warranty. Read and follow label directions and observe all safety precautions in the use of this product. ABRP, Inc., further disclaims, and shall not be liable for, incidental, consequential or indirect damage and/or personal injuries including death arising from the use of this product or the cost of labor involved in its application or any re-application of product that is replaced. SELLER MAKES NO WARRANTY, EXPRESSED OR IMPLIED, CONCERNING THE USE OF THIS PRODUCT OTHER THAN INDICATED ON THE LABEL. BUYER ASSUMES ALL RISK OF USE AND/OR HANDLING OF THIS MATERIAL WHEN SUCH USE AND/OR HANDLING IS CONTRARY TO LABEL INSTRUCTIONS. NO OTHER WARRANTIES ARE MADE, EXPRESSED OR IMPLIED, INCLUDING WITHOUT LIMITATION WARRANTIES AS TO MERCHANTABILITY OR FITNESS FOR

A PARTICULAR PURPOSE. IN ALL EVENTS, ABRP, INC.'S LIABILITY SHALL BE LIMITED SOLELY TO REPLACEMENT OF THE PRODUCT PROVIDED ABOVE. This limited warranty may not be modified or extended by manufacturer's representatives, distributors or dealers of ABRP, Inc., products. This warranty gives the purchaser specific legal rights, as well as rights which may vary from state to state. ABRP, Inc. specifically disclaims any and all other obligations or liability to any party relative to the sale, use or application of its products.

TECHNICAL SERVICES

ABRP, Inc., employs in field technical representatives to answer questions for architects, building owners and contractors.

REFERENCING

Catalog, product specifications, brochures, list of national registered historical landmarks restored with ABRP, Inc., products and video training tapes demonstrating a variety of cleaning and restoration projects being performed with ABRP, Inc. products, are available upon specific request.

ABRP, INC., is on the WORLD WIDE WEB. For more information on many of the specialty building restoration products available to you, please see our home page at <http://www.abrp.com> or e-mail ABRP, Inc. at abrp@abrp.com.

ã Copyright, 2008, American Building Restoration Products, Inc.

