



PRODUCT SPECIFICATIONS



temperature must be 50°F and rising before application. Colder temperatures or below freezing conditions are **NOT** recommended and may produce a cloudy film. Do not apply if rain or heavy moisture will occur just prior to or just after the **PolyShield® Graffiti Preventer Type B** application.

Precautions: read the entire material safety data sheet and product label for a more thorough evaluation of hazards.

PRODUCT NAME

PolyShield® Graffiti Preventer For Unpainted Masonry - Type B

MANUFACTURER

American Building Restoration Products, Inc.
9720 South 60th Street
Franklin, WI 53132
(414) 421-4125
1-800-346-7532 (Orders Only)
Fax (414) 421-8696
www.abrp.com

PRODUCT DESCRIPTION

PolyShield® Graffiti Preventer Type B is a sacrificial coating, formulated to prevent graffiti from penetrating and staining unpainted masonry surfaces.

The invisible **PolyShield® Graffiti Preventer Type B** barrier acts as a shield, preventing absorption of vandalistic harm into the substrate.

It is recommended to apply the **PolyShield® Graffiti Preventer Type B** to graffiti-free surfaces. **PolyShield® Graffiti Preventer Type B** can be applied to all unpainted surfaces including brick, natural stone, concrete, and stucco. **PolyShield® Graffiti Preventer Type B** is designed for interior and exterior use.

Note: Quick and complete removal of graffiti tags will discourage and diminish further vandalism.

Limitations: air and surface

TECHNICAL DATA

Color/Form: opaque tan liquid.

Coverage: 100-300 sq. ft. per gallon for unpainted masonry, depending on the porosity of the surface.

Packaging: one, five and 55 gallon containers.



PROTECT FROM FREEZING

INSTALLATION

Preparatory Work: all surfaces should be free of any existing graffiti as well as any dust or other surface contaminants. A test area should be processed before beginning the overall project. If not satisfied with the result, remove immediately with water and start over. The user shall determine the suitability of the product for its intended use and assumes all risk and liability whatsoever in connection therewith.

APPLICATION

1. Mix **PolyShield® Graffiti Preventer Type B** well before use. Do not thin or mix with additives.
2. Apply **PolyShield® Graffiti Preventer Type B** with a brush, a HVLP sprayer or low pressure hand pump sprayer.
3. Use light spray passes in opposite directions to apply a first coat taking care to back-brush any drips or runs.
4. Allow material to dry for 10 minutes before applying the second coat.

Drying Time: 24 hours

Clean Up: soap and water

REAPPLICATION

If **PolyShield® Graffiti Preventer Type B** is removed during the graffiti removal process, a reapplication of one coat of the **PolyShield® Graffiti Preventer Type B** will only be required to the removed area.

GRAFFITI REMOVAL BEFORE AND AFTER TREATMENT:

When removing existing graffiti, **ABRP, Inc** offers a complete line of graffiti removal products:

- Super Bio Strip®
- 800 Fast Acting
- Tag Zap® Removers
- PolyShield® Strip Soap

AVAILABILITY

Available through a network of distributors and dealers established in cities across the United States and Canada.

NOTICE: the information and recommendations made herein are based on ABRP, Inc., research and the research of others, and are believed to be accurate. However, no guarantee of their accuracy is made because ABRP, Inc., cannot anticipate every possible application of ABRP, Inc., products, nor anticipate every variation encountered in project surfaces, job conditions, and methods used. For this reason, purchasers shall make their own tests to determine the suitability of such products for a particular purpose. Purchasers assume all risk of use, application and handling of products. Statements concerning the possible use of ABRP, Inc., products are not intended as recommendation to use ABRP, Inc., products in the infringement of any patent.

LIMITED WARRANTY

This warranty is valid for one year from the date of product purchase. Purchaser's claims recovery is limited solely to the following warranty from ABRP, Inc., if the product herein is shown to be defective: ABRP, Inc., at its option, will either replace the product or refund the purchase price. Contact ABRP, Inc., to make claim under this warranty. The purchaser must have proof of purchase from the label and the original sales receipt. Proper surface preparation is



American Building Restoration Products, Inc. • Since 1970

ABR[®] PRODUCT SPECIFICATIONS

essential to the product's performance and is a necessary prerequisite for triggering ABRP, Inc.'s obligation under this warranty. Read and follow label directions and observe all safety precautions in the use of this product. ABRP, Inc., further disclaims, and shall not be liable for, incidental, consequential or indirect damage and/or personal injuries including death arising from the use of this product or the cost of labor involved in its application or any re-application of product that is replaced. SELLER MAKES NO WARRANTY, EXPRESSED OR IMPLIED, CONCERNING THE USE OF THIS PRODUCT OTHER THAN INDICATED ON THE LABEL. BUYER ASSUMES ALL RISK OF USE AND/OR HANDLING OF THIS MATERIAL WHEN SUCH USE AND/OR HANDLING IS CONTRARY TO LABEL INSTRUCTIONS. NO OTHER WARRANTIES ARE MADE, EXPRESSED OR IMPLIED, INCLUDING WITHOUT LIMITATION WARRANTIES AS TO MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. IN ALL EVENTS, ABRP, INC.'S LIABILITY SHALL BE LIMITED SOLELY TO REPLACEMENT OF THE PRODUCT PROVIDED ABOVE. This limited warranty may not be modified or extended by manufacturer's representatives, distributors or dealers of ABRP, Inc., products. This warranty gives the purchaser specific legal rights, as well as rights which may vary from state to state. ABRP, Inc. specifically disclaims any and all other obligations or liability to any party relative to the sale, use or application of its products.

TECHNICAL SERVICES

ABRP, Inc., employs in-field technical representatives to answer questions for architects, building owners and contractors.

REFERENCING

Catalog, product specifications, brochures, list of national registered historical landmarks restored with ABRP, Inc., products and video training tapes demonstrating a variety of cleaning and restoration projects being performed with ABRP, Inc. products are available upon

request.

ABRP, INC., is on the WORLD WIDE WEB. For more information on many of the specialty building restoration products available to you, please see our home page at <http://www.abrp.com> or e-mail ABRP, Inc. at abrp@abrp.com.

Copyright, 2009, American Building Restoration Products, Inc.



American Building Restoration Products, Inc. • Since 1970