



MATERIAL SAFETY DATA SHEET
HYDRO SEAL 100

SECTION I - PRODUCT IDENTIFICATION

Manufacturer's Name: American Building Restoration Products, Inc.
9720 S. 60th St.
Franklin, Wisconsin 53132

Emergency Phone No.: Chemtrec 1-800-424-9300

Product Trade Name: Hydro Seal 100

DOT Proper Shipping Name: Petroleum Distillates, N.O.S.
3 UN1268 PG III

SECTION II - HAZARDOUS INGREDIENTS

	CAS NO.	AMT(%)	ACGIH TLV	OSHA PEL
Petroleum Naptha	8032-32-4	90	Not Estab.	Not Estab.
Organo Silane Ester	67764-97-4	8	Not Estab.	Not Estab.
Inert Ingredients		2		

SECTION III - PHYSICAL DATA

Boiling Point: 315-385°F

Vapor Pressure (mm Hg.): 27mm Hg @ 20°C

Vapor Density (Air=1): 4.83

Solubility in Water: Insoluble

Appearance and Odor: Clear, colorless liquid, petroleum odor

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

Flash Point: 105°F = 40.5°C (TCC)

Extinguishing Media: Foam, Carbon Dioxide, Water Spray, or Dry Chemicals.

Special Fire Fighting Procedures: Water spray may be ineffective and can be used to keep containers cool.

SECTION V - HEALTH HAZARD DATA

Threshold Limit Value: See Section II

Effects of Over Exposure:
Dizziness, headache, nose throat irritation may occur. Repeated skin contact will cause dryness. Eye contact causes severe irritation.

EMERGENCY AND FIRST AID PROCEDURES:
SKIN: Wash contacted area with soap and water.



MATERIAL SAFETY DATA SHEET
HYDRO SEAL 100

EYES: Wash immediately with large amounts of water and get medical attention.

INHALATION: Remove to fresh air, if not breathing, use artificial respiration. Seek medical assistance.

INGESTION: DO NOT INDUCE VOMITING. *** SEEK MEDICAL ASSISTANCE

SECTION VI - REACTIVITY DATA

Stability: Stable

Conditions to Avoid: Heat, sparks, open flame and fire

Incompatibility: Strong oxidizing agents.

Hazardous Decomposition Products: N/A

Hazardous Polymerization: Will Not Occur.

SECTION VII - SPILL OR LEAK PROCEDURES

Steps to be taken in case material is released or spilled: Contain spill, eliminate ignition sources and maintain proper ventilation. Absorb small amounts with absorbents such as dirt or vermiculite. Large amounts may be pumped into container for recovery.

WASTE DISPOSAL METHOD: Contact local municipal, state, or federal agencies to ensure compliance of disposal method with current regulations.

NOTE: Empty containers can have residues, gases or mists and are subject to proper waste disposal.

SECTION VIII - SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION: Use a full face chemical cartridge respirator with organic cartridge above 100 ppm.

VENTILATION: Local Exhaust

PROTECTIVE GLOVES: Rubber Gloves

EYE PROTECTION: Close fitting safety goggles.

PROTECTIVE CLOTHING: Wear protective clothing.

SECTION IX - SPECIAL PRECAUTIONS

Precautions to be taken in handling and storing: Keep in cool location.

Avoid physical damage to containers. Emptied containers may contain explosive and harmful vapor. Do not cut container with torch flame, or weld on or near container. Do not reuse container for any purpose until commercially cleaned.



MATERIAL SAFETY DATA SHEET
HYDRO SEAL 100

SECTION X - PREPARATION DATE OF MSDS

Occupational Health & Safety Dept.

Date: 8/25/00
Supersedes: 9/20/95

DISCLAIMER

The information contained herein is based on the data available to us and is believed to be correct. However, American Building Restoration Products, Inc. makes no warranty, expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof. American Building Restoration Products, Inc., assumes no responsibility for injury from the use of the product described herein.

HS100