



MATERIAL SAFETY DATA SHEET
HYDRO SEAL 200

SECTION I - PRODUCT IDENTIFICATION

Manufacturer's Name: American Building Restoration Products, Inc.
9720 S. 60th St.
Franklin, Wisconsin 53132

Emergency Phone Number: Chemtrec 1-800-424-9300

Product Trade Name: Hydro Seal 200

DOT Proper Shipping Name: Petroleum, Distillates, N.O.S.
3 UN1268 PGIII

SECTION II - HAZARDOUS INGREDIENTS

	CAS NO	AMT(%)	OSHA PEL	ACGIH TLV
Petroleum Naptha	8032-32-4	85	Not Estab.	Not Estab.
Organo Silane Ester	N/A	11	Not Estab.	Not Estab.
Inert Ingredients		4		

SECTION III - PHYSICAL DATA

Boiling Point: 315-385°F

Specific Gravity (H₂O=1): .784

Vapor Pressure (mm Hg.): 27

Percent Volatile by Volume (%): N/A

Solubility in Water: Insoluble

Appearance and Odor: Clear, colorless liquid. Petroleum Odor.

SECTION IV - FIRE AND EXPLOSION HAZARD

Flash Point (method used): 105°F (40.5°C.) TCC

Flammable Limits: LEI <1.0% UEI <5.0%

Extinguishing Media: Foam, CO₂, water spray (fog) or dry chemical.

Special Fire Fighting Procedures: Water spray may be ineffective and can be used to keep containers cool.

SECTION V - HEALTH HAZARD DATA

Threshold Limit Value: See Section II

Effects of Over Exposure: Dizziness, headache, nose and throat irritation may occur. Repeated skin contact will cause dryness.

Eye contact with liquid causes severe irritation.

EMERGENCY AND FIRST AID PROCEDURES:



MATERIAL SAFETY DATA SHEET
HYDRO SEAL 200

SKIN: Wash contacted areas with soap and water.

EYE: Wash immediately with large amounts of water and get medical attention.

INHALATION: Remove to fresh air. If not breathing use artificial respiration. Seek medical assistance.

INGESTION: DO NOT INDUCE VOMITING ***** SEEK MEDICAL ASSISTANCE

SECTION IV - REACTIVITY DATA

Stability: Stable

Conditions to Avoid: Heat sparks, open flame and fire.

Incompatibility (Materials to Avoid): Avoid strong oxidizing agents.

Can react violently with chlorine, oxygen or nitric and sulfuric acids

Hazardous Decomposition Products: N/A

Hazardous Polymerization: Will Not Occur.

SECTION VII - SPILL OR LEAK PROCEDURES

Steps to be taken in case material is released or spilled: Contain spill. Eliminate ignition sources. Maintain proper ventilation. Absorb small amounts with absorbent, such as sand, dirt or vermiculite. Large amounts may be pumped into container for recovery.

WASTE DISPOSAL METHOD: Contact local municipal, state or federal agencies to ensure compliance of disposal method with current regulations.

NOTE: Empty containers can have residues, gases or mists and are subject to proper waste disposal.

SECTION VIII - SPECIAL PROTECTION INFORMATION

Respiratory Protection: >100ppm, use airline respiratory or self-contained breathing apparatus; <100ppm. use a full face chemical cartridge respirator with organic vapor cartridge.

Ventilation: Local Exhaust

Protective Gloves: Are required. Made of neoprene, rubber, polyurethane or PVC.

Eye Protection: Chemical goggles or face shield.

Other Protective equipment: An eye wash fountain should be near area where splashing may occur.

SECTION IX - SPECIAL PRECAUTIONS

Precautions to be taken in handling and storing: Keep in cool location. Avoid physical damage to containers. Do not cut container with torch flame, or weld on or near container.



MATERIAL SAFETY DATA SHEET
HYDRO SEAL 200

Do not reuse container for any purpose until commercially cleaned.

SECTION X - PREPARATION DATE OF MSDS

Occupational Health & Safety Dept.

Date: 8/25/00
Supersedes: 3/10/00

DISCLAIMER

The information contained herein is based on the data available to us and is believed to be correct. However, American Building Restoration Products, Inc., makes no warranty, expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof. American Building Restoration Products, Inc., assumes no responsibility for injury from the use of the product described herein.

HS200