



MATERIAL SAFETY DATA SHEET
POLYSHIELD GRAFFITI PREVENTER FOR UNPAINTED MASONRY
- TYPE B -

SECTION I - PRODUCT IDENTIFICATION

Manufacturer's Name: American Building Restoration Products, Inc.
9720 S. 60th Street
Franklin, WI. 53132

Emergency Phone No: Chemtrec 1-800-424-9300

Product Trade Name: Polyshield B Graffiti Preventer for
Unpainted Masonry

DOT Proper Shipping Name: Buffing or Polishing Compound, N.O.S.

SECTION II - HAZARDOUS INGREDIENTS

	CAS NO.	AMT (%)	ACGIH TLV
Dibutyl Phthalate	84-74-2	< 0.3	TWA 5mg/M3

SECTION III - PHYSICAL DATA

Boiling Point: 100°C
Specific Gravity (H₂O=1): Approx 1
Vapor Pressure (mm Hg) 17.5 mm @ 25°C
Percent Volatile By Volume: 82%
Vapor Density (Air=1) Approx 1
Evaporation Rate (water =1): Approx 1
Solubility in water: dispersible
Reactivity in Water: Non-reactive
Appearance and Odor: Light tan emulsion - mild odor.

SECTION IV - FIRE AND EXPLOSION HAZARD

Flash Point: None
Flammable Limits in Air % by volume: N/A
Extinguishing Media: N/A
Special Fire Fighting Procedures: None
Unusual Fire and Explosion Hazards: None
Stability: Stable
Incompatibility (Material to Avoid): None Known

Hazardous Decomposition Products: None Known
Hazardous Polymerization: Will Not Occur



MATERIAL SAFETY DATA SHEET
POLYSHIELD GRAFFITI PREVENTER FOR UNPAINTED MASONRY
- TYPE B -

SECTION V - HEALTH HAZARD DATA

Threshold Limit Value: See Section II

Effects of Over Exposure: None Known

Medical Conditions Generally aggravated by exposure: None Known

EMERGENCY AND FIRST AID PROCEDURES:

INTERNAL: If Swallowed, dilute by drinking 1 or 2 glasses of water or milk. If large amounts are swallowed, induce vomiting. Call physician IMMEDIATELY.

EYES: Flush thoroughly for at least 15 minutes with water followed by a boric acid ophthalmic solution.

SKIN: wash thoroughly with soap and water.

SECTION VI - SPECIAL PROTECTION INFORMATION

Respiratory Protection: Not Required

Ventilation: Normal

Local Exhaust: None

Mechanical (General): None

Protective Gloves: Impervious gloves recommended

Eye Protection: Chemical splash proof goggles

Other Protective Clothing or Equipment: None

SECTION VII - SPECIAL PRECAUTIONS AND SPILL/LEAK PROCEDURES

Precautions to be taken in handling and storage: Keep from freezing

Other Precautions: None

Steps to be taken in case material is released or spilled: Mop up small spills to prevent slipping. Absorb large spills with a suitable absorbent such as soil, sand or commercial absorbent.

WASTE AND DISPOSAL METHOD: Contact local municipal, state, or federal agencies to ensure compliance of disposal method with current regulations.

NOTE: Empty containers can have residues, gases or mists and are subject to proper waste disposal.

SECTION VIII - PREPARATION DATE OF MSDS

Occupational Health & Safety Dept.

Date: 06/06/06
Supersedes: 06/23/03



MATERIAL SAFETY DATA SHEET
POLYSHIELD GRAFFITI PREVENTER FOR UNPAINTED MASONRY
- TYPE B -

DISCLAIMER:

The information contained herein is based on the data available to us and is believed to be correct. However, American Building Restoration Products, Inc. makes no warranty, expressed or implied regarding the use thereof. American Building Restoration Products, Inc. assumes no responsibility for injury from the use of the product described herein.

POLYTYPB