



PRODUCT SPECIFICATIONS



PRODUCT NAME ABR[®]-60 Liquid Latex Binder

MANUFACTURER
American Building Restoration
Products, Inc.
9720 South 60th Street
Franklin, WI 53132
(414) 421-4125
1-800-346-7532 (Orders Only)
Fax (414) 421-8696
www.abrp.com

PRODUCT DESCRIPTION

ABR[®]-60 Liquid Latex Binder is an acrylic liquid polymer specially formulated for use as an additive for Portland cement based mixes and other high alkaline building materials.

ABR[®]-60 Liquid Latex Binder has many uses: provides a tough, self-cured surface for dense concrete and masonry; ensures highest bonding qualities in tuckpointing mortars; improves adhesion; increased bonding; reduces cracking; as an additive to brown and scratch plaster coats to improve trowelability and reduce shrinking cracks; for patching or resurfacing concrete walls, driveways, sidewalks, floors and ramps – interior or exterior.

Typical applications include regular weight and lightweight spray applied coatings, traditional trowel applied stuccos, terrazzo, floor resurfacing and underlayments and basement waterproof coatings.

Cement mortars modified with **ABR[®]-60 Liquid Latex Binder** have

excellent adhesion to a variety of surfaces such as concrete, masonry, brick, wood, rigid polystyrene and polyurethane foam, glass and metals. Can also serve as a high-quality binder for certain non-cement products like one-package tile grouts.

Provides superior adhesion, resistance to UV light and to water, and increased mortar strength, all in a sprayable, low-odor formulation. The addition of **ABR[®]-60 Liquid Latex Binder** makes cement mortars hard, tough and durable to exterior exposure, creating superior flexural, tensile and impact strengths, along with excellent adhesion and resistance to abrasion. This is especially important in thin section applications, such as stuccos, underlayments, and spray coatings, and in applications where heavy traffic and excessive vibration may be involved.

ABR[®]-60 Liquid Latex Binder is a opaque white liquid with a viscosity slightly higher than that of water. It is non-hazardous, non-corrosive and noncombustible.



PROTECT FROM FREEZING

TECHNICAL DATA

Color/Form: opaque liquid.
Storage Requirements: Protect from freezing.
Packaging: one, five and 55 gallon containers.

Blending ratios ABR[®]-60 Liquid Latex Binder to Water

Slurry coats	1/0
Key coats	1/1
Renders	1/3
Repair mortars	1/1
Dry screeds	1/2

Limitations: Do not apply blends modified with **ABR[®]-60 Liquid Latex Binder** to frozen substrates or if the ambient temperature is below 40°F or expected to fall

below 40°F within 24 hours. Do not use with air-entrained cement. Do not use in areas with limited air circulation (i.e. enclosed reservoirs). Keep product from freezing. Keep out of direct sunlight.

INSTALLATION

Preparatory Work: It is important to thoroughly pre-mix the sand and cement to be used. Then **ABR[®]-60 Liquid Latex Binder** is blended together with water. This blend is then added to the sand/cement pre-mixture. Mix everything thoroughly but only for a short time (1-2 minutes) to avoid entraining excessive air. To prevent blend from being overly fluid, part of the water mix should be kept aside and then added slowly to the mixture until the preferred consistency is achieved.

Trial applications must be made to evaluate performance because raw materials (i.e. sand and cement), construction substrates and other application conditions can vary widely.

AVAILABILITY

Available through distributors and dealers across the United States and Canada. **NOTICE:** the information and recommendations made herein are based on ABRP, Inc., research and the research of others, and are believed to be accurate. However, no guarantee of their accuracy is made because ABRP, Inc., cannot anticipate every possible application of ABRP, Inc., products, nor anticipate every variation encountered in project surfaces, job conditions, and methods used. For this reason, purchasers shall make their own tests to determine the suitability of such products for a particular purpose. Purchasers assume all risk of use, application and handling of products. Statements concerning the possible use of ABRP, Inc., products are not intended as recommendation to use ABRP, Inc., products in the infringement of any patent.

LIMITED WARRANTY

This warranty is valid for one year from the date of product purchase. Purchaser's claims recovery is limited solely to the following warranty from ABRP, Inc., if the product herein is shown to be defective: ABRP,



American Building Restoration Products, Inc. • Since 1970



PRODUCT SPECIFICATIONS

Inc., at its option, will either replace the product or refund the purchase price. Contact ABRP, Inc., to make claim under this warranty. The purchaser must have proof of purchase from the label and the original sales receipt. Proper surface preparation is essential to the product's performance and is a necessary prerequisite for triggering ABRP, Inc.'s obligation under this warranty. Read and follow label directions and observe all safety precautions in the use of this product. ABRP, Inc., further disclaims, and shall not be liable for, incidental, consequential or indirect damage and/or personal injuries including death arising from the use of this product or the cost of labor involved in its application or any re-application of product that is replaced. SELLER MAKES NO WARRANTY, EXPRESSED OR IMPLIED, CONCERNING THE USE OF THIS PRODUCT OTHER THAN INDICATED ON THE LABEL. BUYER ASSUMES ALL RISK OF USE AND/OR HANDLING OF THIS MATERIAL WHEN SUCH USE AND/OR HANDLING IS CONTRARY TO LABEL INSTRUCTIONS. NO OTHER WARRANTIES ARE MADE, EXPRESSED OR IMPLIED, INCLUDING WITHOUT LIMITATION WARRANTIES AS TO MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. IN ALL EVENTS, ABRP, INC.'S LIABILITY SHALL BE LIMITED SOLELY TO REPLACEMENT OF THE PRODUCT PROVIDED ABOVE. This limited warranty may not be modified or extended by manufacturer's representatives, distributors or dealers of ABRP, Inc., products. This warranty gives the purchaser specific legal rights, as well as rights which may vary from state to state. ABRP, Inc. specifically disclaims any and all other obligations or liability to any party relative to the sale, use or application of its products.

TECHNICAL SERVICES

ABRP, Inc., employs in-field technical representatives to answer questions for architects, building owners and contractors.

REFERENCING

Catalog, product specifications, brochures, list of national registered historical landmarks restored with ABRP, Inc., products and video training tapes demonstrating a variety of cleaning and restoration projects being performed with ABRP, Inc. products are available upon request. For more information on many of the specialty building restoration products available to you, please see our home page at <http://www.abrp.com> or e-mail ABRP, Inc. at abrp@abrp.com.

Copyright, 2010, American Building Restoration Products, Inc.



American Building Restoration Products, Inc. • Since 1970