Material Safety Data Sheet (MSDS)

Date Issued: January 2, 2014

Date of Last Revision: February 15, 2013

SECTION 1: PRODUCT AND MANUFACTURER INFORMATION

PRODUCT NAME ABR Waterless Cleaning Poultice – Type A

PRODUCT USE Strippable Coating

PRODUCT DESCRIPTION Proprietary natural latex-based compound

MANUFACTURER'S NAME American Building Restoration Products, Inc

MANUFACTURER'S ADDRESS 9720 S 60th St Franklin, WI 53132 CHEMICAL NAME Mixture

CAS NUMBER Not Applicable (mixture)

CHEMICAL FAMILY Not Applicable (mixture)

TELEPHONE 414-421-4125

SECTION 2: COMPOSITION, INFORMATION ON INGREDIENTS

CAS# 9003-31-0

7732-18-5

INGREDIENT

Natural Rubber Latex (Polyisoprene) Water

Note: The balance of the composition is considered to be proprietary.

SECTION 3: HAZARDS IDENTIFICATION

POTENTIAL HAZARDS

This material has a relatively high pH, and may cause burns or irritation if compound comes in contact with skin, eyes, etc. Repeated or prolonged contact of the liquid with skin may cause irritation ranging from redness and itching to blisters. Eye contact with highly alkaline materials may cause irreversible damage to the eye.

The effects of ingestion of natural latex are not known. However, ingestion of a high pH compound in caustic concentrations will cause toxic effects to the central nervous system, and will cause severe stomach distress and possible damage to the digestive tract.

Avoid inhalation of vapors. Avoid contact of vapors with eyes and other sensitive tissues.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE Latex allergies.

CARCINOGENS UNDER OSHA, ACGIH, NTP, IARC, OTHER

None.

SECTION 4: FIRST AID MEASURES

Remove contaminated clothing.

Material Safety Data Sheet (MSDS)

Skin Contact: Rinse with copious amounts of soap and water, and obtain medical attention. Eye Contact: Flush eyes thoroughly with plenty of water. Obtain medical attention immediately. Inhalation: Remove person from area of vapors, and obtain medical attention. Ingestion: Contact physician immediately for treatment advice.

SECTION 5: FIRE AND EXPLOSION INFORMATION

Flash Point and Method:	Not determined
Flammable Limits in Air:	None
Autoignition Temperature:	Not determined
Extinguishing Media:	Water, CO ₂ , or dry chemical for the dried material. The liquid latex is water-based and will not burn as long as it contains a significant concentration of water.
Special Fire Fighting Procedures:	Wear self-contained breathing apparatus approved by NIOSH. Use water spray to keep containers cool, to keep spillage away from fire and heat, and to knock down vapors.
Fire and Explosion Hazards:	Burning dry latex produces dense, black smoke with the potential for producing toxic vapors.
Hazardous Combustion Products:	May include toxic gases such as oxides of carbon.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Confine spill to prevent contamination of streams, ground water, or sewage systems. Absorb liquid onto a suitable absorbent material. Spillage will cause slippery conditions.

Federal, State, and Local regulations must be consulted to determine the proper disposal method for latex compounds.

SECTION 7: HANDLING / STORAGE / TRANSPORTATION

Avoid temperature extremes. Prevent from freezing. Do not allow the temperature of the material to drop below 40°F.

SECTION 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

PERSONAL PROTECTION EQUIPMENT

If permissible exposure limits are exceeded, use a self contained breathing apparatus, a mask supplied with external air, or other NIOSH-approved respiratory protection.

Vinyl or rubber gloves.

Wear coverall chemical splash safety goggles and face shield when possibility exists for eye and face contact due to splashing or spraying materials.

Wear impervious clothing to prevent ANY contact with this material, such as gloves, apron, boots, or full bodysuit as appropriate.

Safety shower and Eye wash stations in work area.

Material Safety Data Sheet (MSDS)

SECTION 9: CHEMICAL AND PHYSICAL PROPERTIES

Appearance and Odor:	White milky paste, characteristic mild acrylic odor.
Boiling Point:	approximately 212°F (water)
Vapor Density:	same as water
Vapor Pressure:	same as water
Solubility in water:	miscible
Freezing Point:	32°F (water)
Specific Gravity at 75°F (w	vater = 1.0) approximately = 0.99
% Volatiles:	Volatile material is water, approximately 40 to 44%.
pH	Typically 11.0 to 12.0

SECTION 10: STABILITY AND REACTIVITY

This material is stable. No hazardous polymerization will occur.

Incompatible Materials and Conditions to Avoid: Solvents, acids, metal salts, and other materials that may coagulate latex. Avoid temperature extremes. Prevent from freezing.

Hazardous Decomposition Products: Thermal decomposition may produce toxic gases, including carbon monoxide, organic acids, aldehydes and alcohols. Avoid heating coagulum above 200°C.

SECTION 11: TOXICOLOGICAL INFORMATION

The only toxicological data available is derived from typical exposure to liquids having a high pH. Therefore, eye contact with the material may cause potentially permanent damage to the affected eyes. Repeated or prolonged skin contact may result in irritation or blistering of the skin.

SECTION 12: ECOLOGICAL INFORMATION

No data available.

Do not discharge to streams, ponds, lakes, or sewers.

SECTION 13: DISPOSAL CONSIDERATIONS

Treatment, storage, transportation, and disposal must be in accordance with applicable Federal, State, and Local regulations.

In case of spillage, soak up with absorbent material, and landfill.

ABR WATERLESS CLEANING POULTICETM Type A

Material Safety Data Sheet (MSDS)

SECTION 14: REGULATORY INFORMATION

U.S. Federal Regulations

TSCA Inventory Status: All components of this product are listed on the TSCA Inventory.

0, minimal, normally stable.

NPCA-HMIS (Hazardous Material Identification System): Health:

1, irritation or minor reversible injury possible.

Flammability: 0, minimal, water-based compound, will not burn as long as significant water content is present.

Reactivity:

Material Safety Data Sheet (MSDS)

Date Issued: January 2, 2014

Date of Last Revision: February 15, 2013

SECTION 1: PRODUCT AND MANUFACTURER INFORMATION

PRODUCT NAME ABR Waterless Cleaning Poultice – Type B

PRODUCT USE Strippable Coating

PRODUCT DESCRIPTION Proprietary natural latex-based compound

MANUFACTURER'S NAME American Building Restoration Products, Inc

MANUFACTURER'S ADDRESS 9720 S 60th St Franklin, WI 53132 CHEMICAL NAME Mixture

CAS NUMBER Not Applicable (mixture)

CHEMICAL FAMILY Not Applicable (mixture)

TELEPHONE 414-421-4125

SECTION 2: COMPOSITION, INFORMATION ON INGREDIENTS

CAS#

INGREDIENT

Natural Rubber Latex (Polyisoprene)9003-31-0Water7732-18-5

Note: The balance of the composition is considered to be proprietary.

SECTION 3: HAZARDS IDENTIFICATION

POTENTIAL HAZARDS

This material has a relatively high pH, and may cause burns or irritation if compound comes in contact with skin, eyes, etc. Repeated or prolonged contact of the liquid with skin may cause irritation ranging from redness and itching to blisters. Eye contact with highly alkaline materials may cause irreversible damage to the eye.

The effects of ingestion of natural latex are not known. However, ingestion of a high pH compound in caustic concentrations will cause toxic effects to the central nervous system, and will cause severe stomach distress and possible damage to the digestive tract.

Avoid inhalation of vapors. Avoid contact of vapors with eyes and other sensitive tissues.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE Latex allergies.

CARCINOGENS UNDER OSHA, ACGIH, NTP, IARC, OTHER

None.

SECTION 4: FIRST AID MEASURES

Remove contaminated clothing.

Material Safety Data Sheet (MSDS)

Skin Contact: Rinse with copious amounts of soap and water, and obtain medical attention. Eye Contact: Flush eyes thoroughly with plenty of water. Obtain medical attention immediately. Inhalation: Remove person from area of vapors, and obtain medical attention. Ingestion: Contact physician immediately for treatment advice.

SECTION 5: FIRE AND EXPLOSION INFORMATION

Flash Point and Method:	Not determined
Flammable Limits in Air:	None
Autoignition Temperature:	Not determined
Extinguishing Media:	Water, CO ₂ , or dry chemical for the dried material. The liquid latex is water-based and will not burn as long as it contains a significant concentration of water.
Special Fire Fighting Procedures:	Wear self-contained breathing apparatus approved by NIOSH. Use water spray to keep containers cool, to keep spillage away from fire and heat, and to knock down vapors.
Fire and Explosion Hazards:	Burning dry latex produces dense, black smoke with the potential for producing toxic vapors.
Hazardous Combustion Products:	May include toxic gases such as oxides of carbon.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Confine spill to prevent contamination of streams, ground water, or sewage systems. Absorb liquid onto a suitable absorbent material. Spillage will cause slippery conditions.

Federal, State, and Local regulations must be consulted to determine the proper disposal method for latex compounds.

SECTION 7: HANDLING / STORAGE / TRANSPORTATION

Avoid temperature extremes. Prevent from freezing. Do not allow the temperature of the material to drop below 40°F.

SECTION 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

PERSONAL PROTECTION EQUIPMENT

If permissible exposure limits are exceeded, use a self contained breathing apparatus, a mask supplied with external air, or other NIOSH-approved respiratory protection.

Vinyl or rubber gloves.

Wear coverall chemical splash safety goggles and face shield when possibility exists for eye and face contact due to splashing or spraying materials.

Wear impervious clothing to prevent ANY contact with this material, such as gloves, apron, boots, or full bodysuit as appropriate.

Safety shower and Eye wash stations in work area.

Material Safety Data Sheet (MSDS)

SECTION 9: CHEMICAL AND PHYSICAL PROPERTIES

Appearance and Odor:	White milky paste, characteristic mild acrylic odor.
Boiling Point:	approximately 212°F (water)
Vapor Density:	same as water
Vapor Pressure:	same as water
Solubility in water:	miscible
Freezing Point:	32°F (water)
Specific Gravity at 75°F (wa	ter = 1.0) approximately = 0.99
% Volatiles:	Volatile material is water, approximately 40 to 44%.
pH	Typically 11.0 to 12.0
Vapor Density: Vapor Pressure: Solubility in water: Freezing Point: Specific Gravity at 75°F (wa % Volatiles:	same as water same as water miscible 32°F (water) tter = 1.0) approximately = 0.99 Volatile material is water, approximately 40 to 44%.

SECTION 10: STABILITY AND REACTIVITY

This material is stable. No hazardous polymerization will occur.

Incompatible Materials and Conditions to Avoid: Solvents, acids, metal salts, and other materials that may coagulate latex. Avoid temperature extremes. Prevent from freezing.

Hazardous Decomposition Products: Thermal decomposition may produce toxic gases, including carbon monoxide, organic acids, aldehydes and alcohols. Avoid heating coagulum above 200°C.

SECTION 11: TOXICOLOGICAL INFORMATION

The only toxicological data available is derived from typical exposure to liquids having a high pH. Therefore, eye contact with the material may cause potentially permanent damage to the affected eyes. Repeated or prolonged skin contact may result in irritation or blistering of the skin.

SECTION 12: ECOLOGICAL INFORMATION

No data available.

Do not discharge to streams, ponds, lakes, or sewers.

SECTION 13: DISPOSAL CONSIDERATIONS

Treatment, storage, transportation, and disposal must be in accordance with applicable Federal, State, and Local regulations.

In case of spillage, soak up with absorbent material, and landfill.

Material Safety Data Sheet (MSDS)

SECTION 14: REGULATORY INFORMATION

U.S. Federal Regulations

TSCA Inventory Status: All components of this product are listed on the TSCA Inventory.

0, minimal, normally stable.

NPCA-HMIS (Hazardous Material Identification System):

1, irritation or minor reversible injury possible.

Flammability: 0, minimal, water-based compound, will not burn as long as significant water content is present.

Reactivity:

Health:

ABR WATERLESS CLEANING POULTICE™ Type C

Material Safety Data Sheet (MSDS)

Date Issued: January 2, 2014

Date of Last Revision: February 15, 2013

SECTION 1: PRODUCT AND MANUFACTURER INFORMATION

PRODUCT NAME ABR Waterless Cleaning Poultice – Type C

PRODUCT USE Strippable Coating

PRODUCT DESCRIPTION Proprietary natural latex-based compound

MANUFACTURER'S NAME American Building Restoration Products, Inc

MANUFACTURER'S ADDRESS 9720 S 60th St Franklin, WI 53132 CHEMICAL NAME Mixture

CAS NUMBER Not Applicable (mixture)

CHEMICAL FAMILY Not Applicable (mixture)

TELEPHONE 414-421-4125

SECTION 2: COMPOSITION, INFORMATION ON INGREDIENTS

CAS# 9003-31-0

7732-18-5

INGREDIENT

Natural Rubber Latex (Polyisoprene) Water

Note: The balance of the composition is considered to be proprietary.

SECTION 3: HAZARDS IDENTIFICATION

POTENTIAL HAZARDS

This material has a relatively high pH, and may cause burns or irritation if compound comes in contact with skin, eyes, etc. Repeated or prolonged contact of the liquid with skin may cause irritation ranging from redness and itching to blisters. Eye contact with highly alkaline materials may cause irreversible damage to the eye.

The effects of ingestion of natural latex are not known. However, ingestion of a high pH compound in caustic concentrations will cause toxic effects to the central nervous system, and will cause severe stomach distress and possible damage to the digestive tract.

Avoid inhalation of vapors. Avoid contact of vapors with eyes and other sensitive tissues.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE Latex allergies.

CARCINOGENS UNDER OSHA, ACGIH, NTP, IARC, OTHER None.

SECTION 4: FIRST AID MEASURES

Remove contaminated clothing.

Material Safety Data Sheet (MSDS)

Skin Contact: Rinse with copious amounts of soap and water, and obtain medical attention. Eye Contact: Flush eyes thoroughly with plenty of water. Obtain medical attention immediately. Inhalation: Remove person from area of vapors, and obtain medical attention. Ingestion: Contact physician immediately for treatment advice.

SECTION 5: FIRE AND EXPLOSION INFORMATION

Flash Point and Method:	Not determined
Flammable Limits in Air:	None
Autoignition Temperature:	Not determined
Extinguishing Media:	Water, CO ₂ , or dry chemical for the dried material. The liquid latex is water-based and will not burn as long as it contains a significant concentration of water.
Special Fire Fighting Procedures:	Wear self-contained breathing apparatus approved by NIOSH. Use water spray to keep containers cool, to keep spillage away from fire and heat, and to knock down vapors.
Fire and Explosion Hazards:	Burning dry latex produces dense, black smoke with the potential for producing toxic vapors.
Hazardous Combustion Products:	May include toxic gases such as oxides of carbon.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Confine spill to prevent contamination of streams, ground water, or sewage systems. Absorb liquid onto a suitable absorbent material. Spillage will cause slippery conditions.

Federal, State, and Local regulations must be consulted to determine the proper disposal method for latex compounds.

SECTION 7: HANDLING / STORAGE / TRANSPORTATION

Avoid temperature extremes. Prevent from freezing. Do not allow the temperature of the material to drop below 40°F.

SECTION 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

PERSONAL PROTECTION EQUIPMENT

If permissible exposure limits are exceeded, use a self contained breathing apparatus, a mask supplied with external air, or other NIOSH-approved respiratory protection.

Vinyl or rubber gloves.

Wear coverall chemical splash safety goggles and face shield when possibility exists for eye and face contact due to splashing or spraying materials.

Wear impervious clothing to prevent ANY contact with this material, such as gloves, apron, boots, or full bodysuit as appropriate.

Safety shower and Eye wash stations in work area.

Material Safety Data Sheet (MSDS)

SECTION 9: CHEMICAL AND PHYSICAL PROPERTIES

Appearance and Odor:	White milky paste, characteristic mild acrylic odor.
Boiling Point:	approximately 212°F (water)
Vapor Density:	same as water
Vapor Pressure:	same as water
Solubility in water:	miscible
Freezing Point:	32°F (water)
Specific Gravity at 75° F (water = 1.0) approximately = 0.99	
% Volatiles:	Volatile material is water, approximately 40 to 44%.
pH	Typically 11.0 to 12.0

SECTION 10: STABILITY AND REACTIVITY

This material is stable. No hazardous polymerization will occur.

Incompatible Materials and Conditions to Avoid: Solvents, acids, metal salts, and other materials that may coagulate latex. Avoid temperature extremes. Prevent from freezing.

Hazardous Decomposition Products: Thermal decomposition may produce toxic gases, including carbon monoxide, organic acids, aldehydes and alcohols. Avoid heating coagulum above 200°C.

SECTION 11: TOXICOLOGICAL INFORMATION

The only toxicological data available is derived from typical exposure to liquids having a high pH. Therefore, eye contact with the material may cause potentially permanent damage to the affected eyes. Repeated or prolonged skin contact may result in irritation or blistering of the skin.

SECTION 12: ECOLOGICAL INFORMATION

No data available.

Do not discharge to streams, ponds, lakes, or sewers.

SECTION 13: DISPOSAL CONSIDERATIONS

Treatment, storage, transportation, and disposal must be in accordance with applicable Federal, State, and Local regulations.

In case of spillage, soak up with absorbent material, and landfill.

ABR WATERLESS CLEANING POULTICETM Type C

Material Safety Data Sheet (MSDS)

SECTION 14: REGULATORY INFORMATION

U.S. Federal Regulations

TSCA Inventory Status: All components of this product are listed on the TSCA Inventory.

NPCA-HMIS (Hazardous Material Identification System):

Health:	1, irritation or minor reversible injury possible.
Flammability:	0, minimal, water-based compound, will not burn as long as significant water content is
	present.
Reactivity:	0 minimal normally stable.

Reactivity