



MATERIAL SAFETY DATA SHEET
GRIP 'N STRIP FAST ACTING

SECTION I - PRODUCT IDENTIFICATION

Manufacturer's Name: American Building Restoration Products, Inc.
9720 S. 60th Street
Franklin, WI. 53132

Emergency Phone Number: Chemtrec 1-800-424-9300

Product Trade Name: Grip 'N Strip Fast Acting

DOT Proper Shipping Name: Potassium Hydroxide Solid,
8 UN1813 PG II

SECTION II - HAZARDOUS INGREDIENTS

	CAS. NO.	AMT(%)	OSHA PEL	ACGIH TLV
Potassium Hydroxide	1310-58-3	61	C2mg/m3	C2mg/m3
2-Hydroxymethylfuran	98-00-0	16		TWA 50 ppm

SECTION III - PHYSICAL DATA

Initial Boiling Point: 133°C
Vapor Pressure: N/A
Vapor Density: N/A
Solubility in Water: Complete
Specific Gravity (H₂O = 1): 1.201
Percent Volatile By Volume: N/A
Evaporation Rate: N/A
Appearance and Odor: Viscous Brownish Paste with Mildly Irritating Odor.

SECTION IV - FIRE AND EXPLOSION HAZARD

Flash Point: N/A
Extinguishing Media: N/A
Special Fire Fighting Procedures: N/A
Unusual Fire & Explosion Hazards: N/A

SECTION V - HEALTH HAZARD DATA

Threshold Limit Value: See Section II
Effects of Over Exposure: Corrosive to skin and mucous membranes.
Causes severe burns.



MATERIAL SAFETY DATA SHEET
GRIP 'N STRIP FAST ACTING

EMERGENCY AND FIRST AID PROCEDURES: Seek first aid in case of contact or suspicion of contact. CALL PHYSICIAN IMMEDIATELY.

EYES: Immediately hold face under running water for twenty minutes with eyes open by force, if necessary. Then cover with clean dressing or sheet. Get prompt medical attention.

SKIN: Flush with plenty of cold water for at least 15 minutes until slipperiness is gone, then wash with vinegar. Apply Orajel Solution to burn.

INGESTION: Drink large quantities of water or milk. Follow with citrus fruit juice, if available. Call Physician immediately.

SECTION VI - REACTIVITY DATA

Stability: Stable

Incompatibility: Mixing with acids, solutions containing ammonium and any active metal such as zinc, aluminum, magnesium, brass or bronze.

Hazardous Decomposition Products: May produce explosive hydrogen.

Hazardous Polymerization: Will Not Occur.

SECTION VII - SPILL OR LEAK PROCEDURES

Shut off leaks if possible without injury. Flush area with water.

Large spills should be diked with earth, then pumped into salvage tank.

WASTE DISPOSAL METHOD: Contact local municipal, state, or federal agencies to ensure compliance of disposal method with current regulations.

NOTE: Empty containers can have residues, gases or mists and are subject to proper waste disposal.

SECTION VIII - SPECIAL PROTECTION INFORMATION

Respiratory Protection: NIOSH approved dust or mist type.

Ventilation: Local Exhaust: If adequate

Mechanical: Steel or plastic type fan

Protective Gloves: Chemical resistant neoprene gauntlet type

Eye Protection: Close fitting splash proof chemical goggles and face shield.

Protective Equipment: Rubber boots, rubber or acid type suit with tight fitting cuffs and collar.

SECTION IX - SPECIAL PRECAUTIONS



MATERIAL SAFETY DATA SHEET
GRIP 'N STRIP FAST ACTING

Precautions to be taken in handling and storing: Store well-contained.
Keep from acids. Freezes (gel) at about 45°F

Other Precautions: Use Caution in handling this material - Avoid
Spills. Do not store in or pipe through any of the above listed
metals.

(See Section VI) Use only mild steel or approved plastic.

SECTION X - PREPARATION DATE OF MSDS

Occupational Health & Safety Dept.

Date: 8/07/01

Supersedes: 2/02/01

DISCLAIMER

The information contained herein is based on the data available to us
and is believed to be correct. However, American Building Restoration
Products, Inc. makes no warranty, expressed or implied from the use
thereof. American Building Restoration Products, Inc. assumes no re-
sponsibility for injury from the use of the product described herein.

800FAGS