



MATERIAL SAFETY DATA SHEET
ABR STRIPIT•ALL

SECTION I - PRODUCT IDENTIFICATION

Manufacturer's Name: American Building Restoration Products, Inc.
9720 S. 60th St.
Franklin, Wisconsin 53132

Emergency Phone No: Chemtrec 1-800-424-9300

Product Trade Name: ABR StripIt•All

DOT Proper Shipping Name: Potassium Hydroxide Solution
8 UN1814 PG II

SECTION II - HAZARDOUS INGREDIENTS

	CAS NO.	AMT(%)	ACGIH TLV	OSHA PEL
Potassium Hydroxide	1310-58-3	4.9	2 mg/m ³	Not Estab.
Monoethanolamine	141-43-5	3.5	3 ppm	TWA 3 ppm
Diethylene Glycol, Monobutyl Ether	112-34-5	7.5	Not Estab.	Not Estab.

SECTION III - PHYSICAL DATA

Boiling Point: 308°F

Specific Gravity (H₂O=1): 1.33

Vapor Pressure (mm Hg.): 1 mm

Percent Volatile By Volume: 51.16

pH: 13.5

Vapor Density: (AIR=1): 3.38

Evaporation Rate: Very Slow

Solubility in Water: Complete Hygroscopic

Appearance: Very viscous, yellow brown semi-paste

SECTION IV - FIRE AND EXPLOSION HAZARD

Flash Point: None

Extinguishing Media: N/A

Special Fire Fighting Procedures: N/A

Unusual Fire and Explosion Hazards: N/A

SECTION V - HEALTH HAZARD DATA

Threshold Limit Value: See Section II



MATERIAL SAFETY DATA SHEET

ABR STRIPIT•ALL

Effects of Over Exposure: Immediate burning of skin, mucous membranes and eye tissues.

EMERGENCY AND FIRST AID PROCEDURES:

Seek first aid in case of contact or suspicion of contact. CALL PHYSICIAN IMMEDIATELY. When seeking medical attention - take label with you.

EYES: Immediately hold face under running water for twenty minutes with

eyes open by force if necessary. Then cover with clean dressing or sheet. Get prompt medical attention.

INTERNAL: Drink several glasses of water. Follow with citrus fruit juice. **Call Physician Immediately.**

EXTERNAL: Flush with plenty of cold water for at least 15 minutes, then wash with vinegar. Flush until slipperiness is gone. Apply Orajel Solution to burn.

SECTION VI - REACTIVITY DATA

Stability: Stable

Incompatibility: Avoid mixing with acid, solutions containing ammonium, and any active metal such as zinc, aluminum, magnesium, brass or bronze.

Hazardous Decomposition Products: May produce explosive hydrogen and violent exothermic reaction.

Hazardous Polymerization: May Occur

Conditions to Avoid: Contact with strong acids.

SECTION VII - SPILL OR LEAK PROCEDURES

Steps to be taken in case material is released or spilled: Shut off leaks if possible without injury. Flush area with water until slipperiness is gone. Large spills should be diked with earth, then pumped into salvage tank.

WASTE AND DISPOSAL METHOD: Contact local municipal, state, or federal agencies to ensure compliance of disposal method with current regulations.

NOTE: Empty containers can have residues, gases or mists and are subject to proper waste disposal.

SECTION VIII - SPECIAL PROTECTION INFORMATION

Respiratory Protection: NOISH - MESA approved dust or mist type



MATERIAL SAFETY DATA SHEET

ABR STRIPIT•ALL

Ventilation: Local Exhaust, if adequate

Mechanical: Steel or plastic fan type

Protective Gloves: Impervious gloves recommended.

Eye Protection: Splash proof-chemical goggles and face shield.

Other Protective Equipment: Rubber or Acid proof suit with tight-fitting cuffs, and collars, rubber boots.

SECTION IX - SPECIAL PRECAUTIONS

Precautions to be taken in handling and storing: Freezes (gel) at about

45°F. Keep away from acids.

Other Precautions: Do not store in or pipe through any of the above listed metals. Use only mild steel or approved plastic.

SECTION X - PREPARATION DATE OF MSDS

Occupational Health & Safety Dept.

Date: 3/26/98

Supersedes: 3/19/98

DISCLAIMER:

The information contained herein is based on the data available to us and is believed to be correct. However, American Building Restoration Products, Inc. makes no warranty, expressed or implied regarding the accuracy of the results to be obtained from the use thereof. American Building Restoration Products, Inc. assumes no responsibility for injury from the use of the product described herein.

ABRSI•A