



PRODUCT SPECIFICATIONS



TECHNICAL DATA

Color/Form: brown gel.

Coverage: 75 to 100 sq. ft. per gallon (1-2 coats of stain).

50 to 75 sq. ft. per gallon (1-2 coats of latex paint or varnish).

50 sq. ft. per gallon (combination of 1-3 coats of latex paint and/or oil paint).

Packaging: one, five and fifty-five gallon containers.

the surface with a fine water spray. A reapplication may be necessary for overhangs, corners, windows and the like where **ABR StripIt-All** tends to move downward and away, therefore reducing the product effectiveness.

REMOVAL

1. If possible, scrape all dissolved residue and discard in an appropriate container. Follow this procedure with a water rinse (hot water works best) ranging from garden hose pressure (which may require some scrubbing) to a high pressure water rinse. On wood, adjust the pressure to 500 psi or lower to avoid damage to the wood fiber. Waiting 24 hours to remove **ABR StripIt-All** requires more rinse time.

2. Once surface has been rinsed it must be neutralized. Apply **X-180 Weathered Wood Restorer** any time after stripping is completed. Apply two applications followed by a complete water rinse from a pressure washer.

3. If wood has become discolored, leave a solution of **X-180 Weathered Wood Restorer** on the discolored area until a crystallized residue appears. Lightly remove crystals from surface without destroying the brightening action of the **X-180 Weathered Wood Restorer** with a very light water rinse.

4. Certain types of wood surfaces may have a raised grain effect after stripping is completed. Very light sanding with 50 grit sandpaper where needed will smooth out this condition. Excessive sanding will close the wood grain, preventing the new finish from penetrating into the wood.

Clean Up: water flush equipment, shrubbery, sidewalks, blacktop, asphalt and other adjacent surfaces immediately upon contact. Leave job site free of any trace amounts of **ABR StripIt-All** or dissolved residue. Never leave behind any containers or equipment. Label appropriate containers of residue for disposal.

PRODUCT NAME **ABR StripIt-All**

MANUFACTURER

American Building Restoration Products, Inc.
9720 South 60th Street
Franklin, WI 53132
(414) 421-4125
1-800-346-7532 (Orders Only)
Fax (414) 421-8696
www.abrp.com

PRODUCT DESCRIPTION

ABR StripIt-All is a water soluble gel designed to remove multiple layers of latex paints, stains, varnishes, linseed oils and other coatings that hide the original color and texture of wood. **ABR StripIt-All** allows you to start over from the beginning by restoring wood to the condition of new lumber before treating the wood with a new finish. (See **X-100 Natural Seal** for a finish/wood preservative). **ABR StripIt-All** removes finishes from all types of surfaces, including masonry and metal. **ABR StripIt-All** requires neutralizing.

Precautions: read the entire Material Safety Data Sheet and product label for a thorough evaluation of hazards. Fully protect all adjacent surfaces including plants and shrubbery. Beware of wind drifting onto auto and pedestrian traffic when rinsing or applying **ABR StripIt-All**. Contact local, state and/or federal agencies to ensure compliance of proper disposal methods and respective regulations.

INSTALLATION

Preparatory Work: it is important to prepare a surface for proper adherence of **ABR StripIt-All**. If dirt or a heavy chalk film is present, rinse the surface with water. Prior to beginning the overall project, a test should be performed to determine the optimum dwell time required for **ABR StripIt-All** to completely penetrate all layers of the finish. The user shall determine the suitability of the product for its intended use and assumes all risk and liability whatsoever in connection therewith.

Example: time required for 1 layer of stain or paint may be 30 minutes. Difficult jobs consisting of multiple layers of paint may require leaving **ABR StripIt-All** on test panels for 3 to 4 hours.

APPLICATION

1. Using a synthetic brush, roller, low pressure sprayer or airless paint sprayer, apply a thick coat of **ABR StripIt-All** to the surface.

Caution: **ABR StripIt-All** is slippery when applied to the surface. Use extreme caution when working on horizontal surfaces.

2. Let **ABR StripIt-All** remain on the surface until all paint or solid color stain has softened. To prevent premature rinsing, wait for the entire surface to become uniformly darkened. This darkened appearance indicates that the **ABR StripIt-All** has dissolved the underlying finish and is ready to be rinsed.

3. If **ABR StripIt-All** has to remain on the surface for 30 minutes or longer, it may dry prematurely. In this instance, moisten dry areas by applying a 50/50 water/**ABR StripIt-All** mix. Then, mist



American Building Restoration Products, Inc. • Since 1970



PRODUCT SPECIFICATIONS

AVAILABILITY

Available through distributors and dealers across the United States and Canada. **NOTICE:** the information and recommendations made herein are based on ABRP, Inc., research and the research of others, and are believed to be accurate. However, no guarantee of their accuracy is made because ABRP, Inc., cannot anticipate every possible application of ABRP, Inc., products, nor anticipate every variation encountered in project surfaces, job conditions, and methods used. For this reason, purchasers shall make their own tests to determine the suitability of such products for a particular purpose. Purchasers assume all risk of use, application and handling of products. Statements concerning the possible use of ABRP, Inc., products are not intended as recommendation to use ABRP, Inc., products in the infringement of any patent.

LIMITED WARRANTY

This warranty is valid for one year from the date of product purchase. Purchaser's claims recovery is limited solely to the following warranty from ABRP, Inc., if the product herein is shown to be defective: ABRP, Inc., at its option, will either replace the product or refund the purchase price. Contact ABRP, Inc., to make claim under this warranty. The purchaser must have proof of purchase from the label and the original sales receipt. Proper surface preparation is essential to the product's performance and is a necessary prerequisite for triggering ABRP, Inc.'s obligation under this warranty. Read and follow label directions and observe all safety precautions in the use of this product. ABRP, Inc., further disclaims, and shall not be liable for, incidental, consequential or indirect damage and/or personal injuries including death arising from the use of this product or the cost of labor involved in its application or any re-application of product that is replaced. **SELLER MAKES NO WARRANTY, EXPRESSED OR IMPLIED, CONCERNING THE USE OF THIS PRODUCT OTHER THAN INDICATED ON THE LABEL. BUYER ASSUMES ALL RISK OF USE AND/OR HANDLING OF THIS MATERIAL**

WHEN SUCH USE AND/OR HANDLING IS CONTRARY TO LABEL INSTRUCTIONS. NO OTHER WARRANTIES ARE MADE, EXPRESSED OR IMPLIED, INCLUDING WITHOUT LIMITATION WARRANTIES AS TO MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. IN ALL EVENTS, ABRP, INC.'S LIABILITY SHALL BE LIMITED SOLELY TO REPLACEMENT OF THE PRODUCT PROVIDED ABOVE. This limited warranty may not be modified or extended by manufacturer's representatives, distributors or dealers of ABRP, Inc., products. This warranty gives the purchaser specific legal rights, as well as rights which may vary from state to state. ABRP, Inc. specifically disclaims any and all other obligations or liability to any party relative to the sale, use or application of its products.

TECHNICAL SERVICES

ABRP, Inc., employs in-field technical representatives to answer questions for architects, building owners and contractors.

REFERENCING

Catalog, product specifications, brochures, list of national registered historical landmarks restored with ABRP, Inc., products and video training tapes demonstrating a variety of cleaning and restoration projects being performed with ABRP, Inc. products are available upon request. For more information on many of the specialty building restoration products available to you, please see our home page at <http://www.abrp.com> or e-mail ABRP, Inc. at abrp@abrp.com.

Copyright, 2010, American Building Restoration Products, Inc.



American Building Restoration Products, Inc. • Since 1970