



Product Specifications

Product Name: 700XX Extra Strength
Special Coating Stripper

Manufacturer: American Building Restoration Products, Inc.



PRODUCT DESCRIPTION: 700XX is ideal for the removal of paint, varnish, epoxy, polyurethane & marine finishes. 700XX stripper does not require neutralization after the stripping process. 700XX is a methylene chloride based gel designed for certain types of coatings that will not dissolve with a strong caustic stripper. 700XX works fast to strip elastomeric coatings, epoxies and swimming pool chlorinates. 700XX will not darken wood. Due to its gel consistency, 700XX will not rapidly dry, allowing for extended removability.

LIMITATIONS: 700XX will dry out in direct sun light, reducing its effectiveness. Optimum working temperature is 55-75°F. Product efficiency is reduced below a temperature of 40°F. 700XX will not dissolve inorganic cementitious coatings.

PRECAUTIONS: Read the entire material safety data sheet and product label for a more thorough evaluation of hazards. Fully protect all adjacent surfaces, especially asphalt, plastic, rubber, tile, linoleum and anodized aluminum as well as general work area. Methylene chloride strippers produce their own gas when activated with air, sunlight, etc. They have been known to explode in airless paint sprayers and other types of pressure vessels. Ensure proper ventilation while using 700XX. If a medium or strong odor is detected, or should you experience slight dizziness or nausea, STOP! Ventilation is inadequate. Open all windows and doors to provide cross ventilation until the odor and/or side effects are eliminated. Prevent contact with eyes and/or skin. Wear rubber gloves to protect the skin and chemical splash proof goggles to protect the eyes while using 700XX.

TECHNICAL DATA: Color/Form: Amber gel.

COVERAGE: 50 sq. ft. per gallon, depending upon surface layers to be removed.

PACKAGING: Quart, one, five and fifty-five gallon containers.

SHELF LIFE: 6 months to one year.

INSTALLATION: A test area should be performed prior to beginning overall project to determine optimum dwell time for the product and the number of applications necessary to completely remove all traces of finish from the surface. User shall determine the suitability of the product for its intended use and assumes all risk and liability whatsoever in connection therewith. Follow all local, state, or federal disposal regulations when using this product.

APPLICATION: 1. Apply 700XX using a natural bristle brush or roller. 2. Apply a thick, uniform coat of 700XX to the surface to be stripped. 3. 700XX continues to penetrate and dissolve as long as the product remains wet. **NOTE:** Temperature, air flow, direct sunlight, etc. can evaporate 700XX. 4. Dab additional 700XX on dry spots to maintain an even, active application. (This may need to be done several times during the first application). **NOTE:** When stripping floors, cover area with polyethylene sheeting to reduce drying and aid in penetration. 5. Let 700XX work until finish is completely loosened. (Dwell time is approximately 25-30 minutes or as determined by your test). 6. Use a wide blade putty knife to scrape off dissolved finish and a stripper brush to clean out carved or grooved areas. **NOTE:** If the finish needs further removal, apply another coat of 700XX to the surface. Wait 10-15 minutes and test for removal. 7. 700XX should be rinsed immediately after it dissolves the finish. Using #3 coarse steel wool and warm water, surface should be rinsed from the bottom up. Do not use water rinse method on veneer surfaces. 8. Wipe clean with a dry cloth.

AVAILABILITY: Available through distributors and dealers across the United States and Canada.

NOTICE: The information and recommendations made herein are based on ABRP, Inc., research and the research of others, and are believed to be accurate. However, no guarantee of their accuracy is made because ABRP, Inc., cannot anticipate every possible application of ABRP, Inc., products, nor anticipate every variation encountered in project surfaces, job conditions, and methods used. For this reason, purchasers shall make their own tests to determine the suitability of such products for a particular purpose. Purchasers assume all risk of use, application and handling of products. Statements concerning the possible use of ABRP, Inc., products are not intended as recommendation to use ABRP, Inc., products in the infringement of any patent.

LIMITED WARRANTY: This warranty is valid for one year from the date of product purchase. Purchaser's claims recovery is limited solely to the following warranty from ABRP, Inc., if the product herein is shown to be defective: ABRP, Inc., at its option, will either replace the product or refund the purchase price. Contact ABRP, Inc., to make claim under this warranty. The purchaser must have proof of purchase from the label and the original sales receipt. Proper surface preparation is essential to the product's performance and is a necessary prerequisite for triggering ABRP, Inc.'s obligation under this warranty. Read and follow label directions and observe all safety precautions in the use of this product. ABRP, Inc., further disclaims, and shall not be liable for, incidental, consequential or indirect damage and/or personal injuries including death arising from the use of this product or the cost of labor involved in its application or any reapplication of product that is replaced. SELLER MAKES NO WARRANTY, EXPRESSED OR IMPLIED, CONCERNING THE USE OF THIS PRODUCT OTHER THAN INDICATED ON THE LABEL. BUYER ASSUMES ALL RISK OF USE AND/OR HANDLING OF THIS MATERIAL WHEN SUCH USE AND/OR HANDLING IS CONTRARY TO LABEL INSTRUCTIONS. NO OTHER WARRANTIES ARE MADE, EXPRESSED OR IMPLIED, INCLUDING WITHOUT LIMITATION WARRANTIES AS TO MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. IN ALL EVENTS, ABRP, INC.'S LIABILITY SHALL BE LIMITED SOLELY TO REPLACEMENT OF THE PRODUCT PROVIDED ABOVE. This limited warranty may not be modified or extended by manufacturer's representatives, distributors or dealers of ABRP, Inc., products. This warranty gives the purchaser specific legal rights, as well as rights which may vary from state to state. ABRP, Inc. specifically disclaims any and all other obligations or liability to any party relative to the sale, use or application of its products.

TECHNICAL SERVICES: ABRP, Inc., employs in-field technical representatives to answer questions for architects, building owners and contractors.

REFERENCING: Catalog, product specifications, brochures, list of national registered historical landmarks restored with ABRP, Inc., products and video training tapes demonstrating a variety of cleaning and restoration projects being performed with ABRP, Inc. products are available upon request. For more information on many of the specialty building restoration products available to you, please see our website at www.abrp.com or e-mail ABRP, Inc. at abrp@abrp.com.

American Building Restoration Products, Inc. • address: 9720 S. 60th St., Franklin, WI 53132

Corporate office: (414) 421-4125 • **Orders ONLY:** 1-800-346-7532 • **fax:** (414) 421-8696 • **email:** abrp@abrp.com • **website:** abrp.com

Updated: 7/27/2010 • Copyright © 2010 American Building Restoration Products, Inc.