



Product Specifications

Product Name: ABR® Citrus Paint Remover

Manufacturer: American Building Restoration Products, Inc.

PRODUCT DESCRIPTION: ABR® Citrus Paint Removers are designed to remove multiple layers of latex paint, oil paint, varnish, stain and other finishes from wood, masonry, plastered walls or metal in a single application. ABR® Citrus Paint Removers are a unique development in the paint and coating removal industry. ABR® Citrus Paint Removers do NOT contain methylene chloride and offer a fresh citrus scent. The formulas are recommended for both interior and exterior use. No neutralizing is needed. The formulas are non-damaging to wood, masonry, plastered walls and metal. **NOTE:** ABR® Citrus Paint Removers may damage or soften asphalt, plastic, rubber, tile, linoleum and adjacent painted surfaces. In some cases, ABR® Citrus Paint Removers Paste can be reused for multiple applications. ABR® Citrus Paint Removers are ideal for intricate carvings, moldings, pillars, fine furniture and antiques. When applied uniformly, ABR® Citrus Paint Removers penetrate multiple layers of paint mil thickness and reduce the water rinse normally needed to dissolve stripper residue. The special paste formula stays wet and active longer than conventional strippers. In some cases, the paste formula may be removed and reused on multiple surfaces of your current stripping project. ABR® Citrus Paint Remover Liquid is ideal for refinishing work and will remove thin layers of varnish, stain and graffiti. The liquid formula can also be used for the clean-up of paint splatters. ABR® Citrus Paint Removers Paste may also be used as a poltice stain remover for embedded graffiti stains. It is also great for removing mastics, decals and traffic markers.

PRECAUTIONS: Read the entire material safety data sheet and product label for a thorough evaluation of hazards. Fully protect all adjacent surfaces including vegetation from coming in direct contact with ABR® Citrus Paint Removers. When stripping interiors, lay plastic sheeting on the floor and cover with stacks of newspaper or cardboard to absorb scraped residue. **USE ONLY WITH ADEQUATE VENTILATION!** Close container after each use. Avoid inhalation and use only with adequate ventilation. If using indoors, open all windows and doors and make sure there is fresh air movement. If adequate ventilation cannot be maintained, wear respiratory protection or leave the area. **CAUTION!** This product is combustible. Keep away from heat, sparks, flame and all other sources of ignition. Eye Protection Required when using ABR® Citrus Paint Removers. Wear chemical splash proof goggles.

TECHNICAL DATA: Color/Form: ABR® Citrus Paint Remover Paste: Putty- Colored thick paste. ABR® Citrus Paint Remover: Gelclear gel. ABR® Citrus Paint Remover Liquid: Clear liquid.

COVERAGE: NOTE: Product may be reusable on some finishes, increasing the amount of coverage per gallon. The amount of coverage may also vary depending on

the surface and the layers of finished to be stripped. ABR® Citrus Paint Remover Paste- 25 to 75 square feet per gallon. ABR® Citrus Paint Remover Gel- 75 to 125 square feet per gallon. ABR® Citrus Paint Remover Liquid- 200 to 250 square feet per gallon.

PACKAGING: One and five gallon containers.

INSTALLATION PREPARATORY WORK: Prepare a surface free from dirt and oil. Prior to beginning the overall project, a test should be performed to determine the optimum dwell time for the product, the number of applications necessary to completely remove all traces of finish from the surface, and if any ABR® Citrus Paint Removers may be reused for additional application(s). The user shall determine the suitability of the product for its intended use and assumes all risk and liability whatsoever in connection therewith.

APPLICATION: 1. A. ABR® Citrus Paint Remover Paste: Approximately 1/8- 1/4 inch thick with a trowel or brush. B. Apply ABR® Citrus Paint Remover Gel with a natural bristle brush, roller or airless sprayer. C. Apply ABR® Citrus Paint Remover Liquid with a natural bristle brush, roller or HVLP sprayer. 2. Allow ABR® Citrus Paint Removers to remain on the surface until all paint is dissolved. ABR® Citrus Paint Removers will penetrate an average of one (1) layer of paint every fifteen (15) to thirty (30) minutes. **NOTE:** ABR® Citrus Paint Remover Paste and Gel should be applied in temperature range between 50°F to 75°F for product efficiency. If possible, avoid direct sunlight application. For best results, apply in late afternoon during cooler temperatures. ABR® Citrus Paint Remover Paste and Gel may sag if applied too thickly over latex finishes. If sagging occurs, apply thinner coats of ABR® Citrus Paint Remover. Allow the product to dwell for one (1) hour and apply a second coat directly on top of the first coat.

REMOVAL: 1. Scrape away the dissolved residue. Forming a membrane may require leaving ABR® Citrus Paint Remover on the surface beyond 24 hours depending on the temperature and humidity. Rinse the surface with a clean sponge or scrub brush and clean water to remove excess ABR® Citrus Paint Remover residue. **NOTE:** Beware of wind drift onto adjacent surfaces while rinsing or applying ABR® Citrus Paint Removers. A soft wire brush may be used to remove dried product missed during rinsing. 2. ABR® Citrus Paint Removers do not require neutralization.

STORAGE: ABR® Citrus Paint Removers should always be stored in the container in which it was purchased.

DISPOSAL: Contact local, state and/or federal agencies to ensure compliance with regulations governing the disposal of this product along with coatings and finishes that may be removed when using this product.

AVAILABILITY: Available through a network of distributors, dealers and representatives established

in principal cities across the United States, Canada and Japan.

NOTICE: The information and recommendations made herein are based on ABRP, Inc., research and the research of others, and are believed to be accurate. However, no guarantee of their accuracy is made because ABRP, Inc., cannot anticipate every possible application of ABRP, Inc., products, nor anticipate every variation encountered in project surfaces, job conditions, and methods used. For this reason, purchasers shall make their own tests to determine the suitability of such products for a particular purpose. Purchasers assume all risk of use, application and handling of products. Statements concerning the possible use of ABRP, Inc., products are not intended as recommendation to use ABRP, Inc., products in the infringement of any patent.

LIMITED WARRANTY: This warranty is valid for one year from the date of product purchase. Purchaser's claims recovery is limited solely to the following warranty from ABRP, Inc., if the product herein is shown to be defective: ABRP, Inc., at its option, will either replace the product or refund the purchase price. Contact ABRP, Inc., to make claim under this warranty. The purchaser must have proof of purchase from the label and the original sales receipt. Proper surface preparation is essential to the product's performance and is a necessary prerequisite for triggering ABRP, Inc.'s obligation under this warranty. Read and follow label directions and observe all safety precautions in the use of this product. ABRP, Inc., further disclaims, and shall not be liable for, incidental, consequential or indirect damage and/or personal injuries including death arising from the use of this product or the cost of labor involved in its application or any reapplication of product that is replaced. **SELLER MAKES NO WARRANTY, EXPRESSED OR IMPLIED, CONCERNING THE USE OF THIS PRODUCT OTHER THAN INDICATED ON THE LABEL. BUYER ASSUMES ALL RISK OF USE AND/OR HANDLING OF THIS MATERIAL WHEN SUCH USE AND/OR HANDLING IS CONTRARY TO LABEL INSTRUCTIONS. NO OTHER WARRANTIES ARE MADE, EXPRESSED OR IMPLIED, INCLUDING WITHOUT LIMITATION WARRANTIES AS TO MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. IN ALL EVENTS, ABRP, INC.'S LIABILITY SHALL BE LIMITED SOLELY TO REPLACEMENT OF THE PRODUCT PROVIDED ABOVE.** This limited warranty may not be modified or extended by manufacturer's representatives, distributors or dealers of ABRP, Inc., products. This warranty gives the purchaser specific legal rights, as well as rights which may vary from state to state. ABRP, Inc. specifically disclaims any and all other obligations or liability to any party relative to the sale, use or application of its products.

TECHNICAL SERVICES: ABRP, Inc., employs in-field technical representatives to answer questions for architects, building owners and contractors.

REFERENCING: Catalog, product specifications, brochures, list of national registered historical landmarks restored with ABRP, Inc., products and video training tapes demonstrating a variety of cleaning and restoration projects being performed with ABRP, Inc. products are available upon request. *For more information on many of the specialty building restoration products available to you, please see our website at www.abrp.com or e-mail ABRP, Inc. at abrp@abrp.com.*

American Building Restoration Products, Inc. • address: 9720 S. 60th St., Franklin, WI 53132

Corporate office: (414) 421-4125 • Orders ONLY: 1-800-346-7532 • fax: (414) 421-8696 • email: abrp@abrp.com • website: abrp.com