



Product Specifications



Product Name: PolyShield® Regular Graffiti Preventer

Manufacturer: American Building Restoration Products, Inc.

PRODUCT DESCRIPTION: PolyShield® Regular Graffiti Preventer is an invisible, sacrificial coating formulated to prevent graffiti from damaging painted surfaces. PolyShield® Regular Graffiti Preventer also prevents oxidation to painted aluminum, restores faded painted surfaces and reduces dirt build up. It is recommended to apply PolyShield® Regular Graffiti Preventer to graffiti-free surfaces. PolyShield® Regular Graffiti Preventer can be applied to all interior and exterior painted surfaces including wood, aluminum, metal, vinyl, brick, concrete, and stucco. PolyShield® Regular Graffiti Preventer works great on student lockers, bathroom walls, signs, bus stops, bus interiors and any other painted surface that can be defaced with graffiti.

LIMITATIONS: Air and surface temperature must be 50°F and rising before application. Colder temperatures or below freezing conditions are NOT recommended and may produce a cloudy film. Do not apply if rain or heavy moisture will occur just prior to or just after the PolyShield® Regular Graffiti Preventer application.

PRECAUTIONS: Read the entire material safety data sheet and product label for a more thorough evaluation of hazards.

TECHNICAL DATA: Color/Form: Opaque tan liquid.

COVERAGE: On painted surfaces 1,000 to 1,500 sq. ft. per gallon depending on the finish and the porosity of the surface.

PACKAGING: One, five and 55 gallon containers.



PROTECT FROM FREEZING

NOTE: Quick and complete removal of graffiti tags can discourage and diminish further vandalism. Removal of graffiti from painted surfaces requires some skill, as the paint and the graffiti tag will be affected by the solvent action of the graffiti remover. Painting over graffiti may result in the tag pigment bleeding through. Remove the graffiti tag, paint if necessary and apply the PolyShield® Regular Graffiti Preventer.

INSTALLATION PREPARATORY WORK: All surfaces should be free of any existing graffiti as well as any dust or other surface contaminants. A test area should be processed before beginning the overall project. If not satisfied with the result, remove immediately with water and start over. The user shall determine the suitability of the product for its intended use and assumes all risk and liability whatsoever in connection therewith.

INITIAL TREATMENT APPLICATION: Apply 2 coats of PolyShield® Regular Graffiti Preventer to graffiti free surface. Allow 10 minutes for the first coat to dry before application of the second coat.

WIPE ON METHOD: Apply PolyShield® Regular Graffiti Preventer with a sponge or cloth. This method will produce a shine.

CONVENTIONAL SPRAY METHOD OR DETAIL GUN: Use light passes to apply PolyShield® Regular Graffiti Preventer in opposite directions. Reduce material to a fog, using only 60/70 pounds of air pressure. Do not apply in heavy coats. This method will produce a flat finish.

NOTE: Using an airless paint sprayer, hand pump garden type sprayer or flood type application will NOT produce satisfactory results.

DRYING TIME: 24 hours.

CLEAN UP: Soap and water.

REAPPLICATION: If PolyShield® Regular Graffiti Preventer is removed during the graffiti removal process, a reapplication of one coat of the PolyShield® Regular Graffiti Preventer will only be required to the removed area.

GRAFFITI REMOVAL BEFORE AND AFTER TREATMENT: When removing existing graffiti, ABRP, Inc offers a complete line of graffiti removal products:

- Super Bio Strip®
- 800 Fast Acting
- Tag Zap® Removers
- PolyShield® Strip Soap

AVAILABILITY: Available through distributors and dealers across the United States and Canada.

NOTICE: The information and recommendations made herein are based on ABRP, Inc., research and the research of others, and are believed to be accurate. However, no guarantee of their accuracy is made because ABRP, Inc., cannot anticipate every possible application of ABRP, Inc., products, nor anticipate every variation encountered in project surfaces, job conditions, and methods used. For this reason, purchasers shall make their own tests to determine the suitability of such products for a particular purpose. Purchasers assume all risk of use, application and handling of products. Statements concerning the possible use of ABRP, Inc., products are not intended as recommendation to use ABRP, Inc., products in the infringement of any patent.

LIMITED WARRANTY: This warranty is valid for one year from the date of product purchase. Purchaser's claims recovery is limited solely to the following warranty from ABRP, Inc., if the product herein is shown to be defective: ABRP, Inc., at its option, will either replace the product or refund the purchase price. Contact ABRP, Inc., to make claim under this warranty. The purchaser must have proof of purchase from the label and the original sales receipt. Proper surface preparation is essential to the product's performance and is a necessary prerequisite for triggering ABRP, Inc.'s obligation under this warranty. Read and follow label directions and observe all safety precautions in the use of this product. ABRP, Inc., further disclaims, and shall not be liable for, incidental, consequential or indirect damage and/or personal injuries including death arising from the use of this product or the cost of labor involved in its application or any reapplication of product that is replaced. SELLER MAKES NO WARRANTY, EXPRESSED OR IMPLIED, CONCERNING THE USE OF THIS PRODUCT OTHER THAN INDICATED ON THE LABEL. BUYER ASSUMES ALL RISK OF USE AND/OR HANDLING OF THIS MATERIAL WHEN SUCH USE AND/OR HANDLING IS CONTRARY TO LABEL INSTRUCTIONS. NO OTHER WARRANTIES ARE MADE, EXPRESSED OR IMPLIED, INCLUDING WITHOUT LIMITATION WARRANTIES AS TO MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. IN ALL EVENTS, ABRP, INC.'S LIABILITY SHALL BE LIMITED SOLELY TO REPLACEMENT OF THE PRODUCT PROVIDED ABOVE. This limited warranty may not be modified or extended by manufacturer's representatives, distributors or dealers of ABRP, Inc., products. This warranty gives the purchaser specific legal rights, as well as rights which may vary from state to state. ABRP, Inc. specifically disclaims any and all other obligations or liability to any party relative to the sale, use or application of its products.

TECHNICAL SERVICES: ABRP, Inc., employs in-field technical representatives to answer questions for architects, building owners and contractors.

REFERENCING: Catalog, product specifications, brochures, list of national registered historical landmarks restored with ABRP, Inc., products and video training tapes demonstrating a variety of cleaning and restoration projects being performed with ABRP, Inc. products are available upon request. For more information on many of the specialty building restoration products available to you, please see our website at www.abrp.com or e-mail ABRP, Inc. at abrp@abrp.com.

American Building Restoration Products, Inc. • address: 9720 S. 60th St., Franklin, WI 53132

Corporate office: (414) 421-4125 • Orders ONLY: 1-800-346-7532 • fax: (414) 421-8696 • email: abrp@abrp.com • website: abrp.com

Updated: 10/13/2009 • Copyright © 2009 American Building Restoration Products, Inc.