



# Product Specifications

**Product Name:** ABR Waterless Cleaning Poultice®

**Manufacturer:** American Building Restoration Products, Inc.

**PRODUCT DESCRIPTION:** ABR Waterless Cleaning Poultice™ is a temporary cleaning coating designed to remove dirt on a wide variety of surfaces, both interior and exterior where an unconventional cleaning method is needed. This removable coating requires no water in its application or removal. ABR Waterless Cleaning Poultice™ collects dirt and contaminants removed from the substrate surface within the coating for easy collection and disposal. ABR Waterless Cleaning Poultice™ may be used on interior and exterior surfaces including, but not limited to, painted or bare metal, brick, textured stone, concrete, marble, ceramic, terrazzo, slate, limestone, granite, tile and plastic. The creamy consistency and opaque color of the ABR Waterless Cleaning Poultice™ allows for an even and “easy to see” application.

**TECHNICAL DATA:** Color/Form: Cream colored viscous liquid.

**COVERAGE:** Approx 50-75 sq. ft. per gallon at 1/16” dry depending on the porosity of the surface and the contaminants to be removed. Packaging: Five gallon containers Storage Requirements: 50°-100°F ABR Waterless Cleaning Poultice™ freezes at 32°F. If ABR Waterless Cleaning Poultice™ freezes it will no longer be usable.



## PROTECT FROM FREEZING

**LATEX ALLERGY NOTICE:** ABR Waterless Cleaning Poultice™ contains latex (a natural fluid produced by the rubber tree) and may cause allergic reactions in some people. Symptoms include an itchy rash, redness, blisters and scaling, or in more severe cases, dropping blood pressure, swelling of the throat and tongue and difficulty breathing. Seek immediate medical attention if symptoms persist. ABR Waterless Cleaning Poultice™ is blended with special additives designed to remove a wide variety of stains created by the accumulation of dirt and other atmospheric contaminants. ABR Waterless Cleaning Poultice™ is available in three (3) manufactured strengths: **Type A** – suitable for use in most interior applications where light to moderate pollutants and/or dirt accumulation is present. **Type B** – suitable for use in most interior or exterior applications where moderate to heavy pollutants and/or staining is present. **Type C** – suitable for use in most interior or exterior applications where heavy or deeply embedded pollutants and/or staining is present. **Type D** – (Custom Blend) Contact our technical support team for a custom evaluation of your specific project.

**INSTALLATION LIMITATIONS:** ABR Waterless Cleaning Poultice™ should not be applied when the air or surface temperature is below 50°F, or if rain or

heavy moisture is forecasted. Do not use on carpeting or fabric. Do not use on any stained wood surface as discoloration may occur. Do not thin.

**PREPARATORY WORK:** User shall determine the suitability of the product for its intended use and assumes all risk and liability whatsoever in connection therewith. A test area should be processed prior to beginning the overall project to determine precise procedures necessary for most effective results and compatibility to surface being treated. Allow the test area to thoroughly dry then test the ABR Waterless Cleaning Poultice™ for ease of removal and overall results. This is especially important when temperatures are approaching or above 80°F as the ABR Waterless Cleaning Poultice™ may cure in only a few hours.

**APPLICATION:** Surface must be dry. 1. Apply at a temperature of 50°F or higher. 2. Apply a liberal 1/16” thick coat to the surface with a brush, spatula, roller or designated airless spray equipment. Apply evenly to avoid a thin, feathered edge. 3. For best results, agitation of the surface immediately after application will increase the cleaning action. While the product is wet agitate the surface with a stiff synthetic brush, especially over heavily soiled areas. Dirt and grime will be pulled into the ABR Waterless Cleaning Poultice™ while agitation takes place. After agitation, smooth the surface with additional ABR Waterless Cleaning Poultice™ to create an even film. Spray applications of ABR Waterless Cleaning Poultice™ can be made using an appropriate airless texture sprayer with a max working pressure of 3300psi, a tip size 27/1000 to 33/1000 depending on desired coating thickness. 4. The ABR Waterless Cleaning Poultice™ does not require water in its application or removal; however, it is not water incompatible. For example, you may find it helpful to agitate a heavily soiled surface with a water dampened brush to prevent premature drying. 5. Allow the ABR Waterless Cleaning Poultice™ to fully dry a minimum of 6 hours on the surface. Depending on substrate and amount of contaminates to be removed a 12 to 72 hour curing time may be required. 6. To remove the dried ABR Waterless Cleaning Poultice™, start at a corner and peel the film away from the surface. 7. Following removal, wipe down treated areas with a damp sponge to remove any remaining residue.

**NOTE:** To ensure the ease of removal, remove from the surface within 3 days of the initial date of application. Thin applications of ABR Waterless Cleaning Poultice™ may be difficult to remove and may require the use of the ABR Citrus Paint Remover Liquid®.

**CLEAN UP & DISPOSAL:** Rinse brush, roller or sprayer in a pail with water and dish detergent. Do not pour down drain. Dispose of in accordance with state, local and federal regulations.

**AVAILABILITY:** Available through distributors and dealers across the United States and Canada.

**NOTICE:** The information and recommendations made herein are based on ABRP, Inc., research and the research of others, and are believed to be accurate. However, no guarantee of their accuracy is made because ABRP, Inc., cannot anticipate every possible application of ABRP, Inc., products, nor anticipate every variation encountered in project surfaces, job conditions, and methods used. For this reason, purchasers shall make their own tests to determine the suitability of such products for a particular purpose. Purchasers assume all risk of use, application and handling of products. Statements concerning the possible use of ABRP, Inc., products are not intended as recommendation to use ABRP, Inc., products in the infringement of any patent.

**LIMITED WARRANTY:** This warranty is valid for one year from the date of product purchase. Purchaser's claims recovery is limited solely to the following warranty from ABRP, Inc., if the product herein is shown to be defective: ABRP, Inc., at its option, will either replace the product or refund the purchase price. Contact ABRP, Inc., to make claim under this warranty. The purchaser must have proof of purchase from the label and the original sales receipt. Proper surface preparation is essential to the product's performance and is a necessary prerequisite for triggering ABRP, Inc.'s obligation under this warranty. Read and follow label directions and observe all safety precautions in the use of this product. ABRP, Inc., further disclaims, and shall not be liable for, incidental, consequential or indirect damage and/or personal injuries including death arising from the use of this product or the cost of labor involved in its application or any reapplication of product that is replaced. SELLER MAKES NO WARRANTY, EXPRESSED OR IMPLIED, CONCERNING THE USE OF THIS PRODUCT OTHER THAN INDICATED ON THE LABEL. BUYER ASSUMES ALL RISK OF USE AND/OR HANDLING OF THIS MATERIAL WHEN SUCH USE AND/OR HANDLING IS CONTRARY TO LABEL INSTRUCTIONS. NO OTHER WARRANTIES ARE MADE, EXPRESSED OR IMPLIED, INCLUDING WITHOUT LIMITATION WARRANTIES AS TO MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. IN ALL EVENTS, ABRP, INC.'S LIABILITY SHALL BE LIMITED SOLELY TO REPLACEMENT OF THE PRODUCT PROVIDED ABOVE. This limited warranty may not be modified or extended by manufacturer's representatives, distributors or dealers of ABRP, Inc., products. This warranty gives the purchaser specific legal rights, as well as rights which may vary from state to state. ABRP, Inc. specifically disclaims any and all other obligations or liability to any party relative to the sale, use or application of its products.

**TECHNICAL SERVICES:** ABRP, Inc., employs in-field technical representatives to answer questions for architects, building owners and contractors.

**REFERENCING:** Catalog, product specifications, brochures, list of national registered historical landmarks restored with ABRP, Inc., products and video training tapes demonstrating a variety of cleaning and restoration projects being performed with ABRP, Inc. products are available upon request. For more information on many of the specialty building restoration products available to you, please see our website at [www.abrp.com](http://www.abrp.com) or e-mail ABRP, Inc. at [abrp@abrp.com](mailto:abrp@abrp.com).

**American Building Restoration Products, Inc. • address: 9720 S. 60th St., Franklin, WI 53132**

**Corporate office: (414) 421-4125 • Orders ONLY: 1-800-346-7532 • fax: (414) 421-8696 • email: [abrp@abrp.com](mailto:abrp@abrp.com) • website: [abrp.com](http://abrp.com)**

Updated: 6/21/2013 • Copyright © 2013 American Building Restoration Products, Inc.