



Product Specifications



Product Name: TR-7 Tar & Mastic Remover

Manufacturer: American Building Restoration Products, Inc.

PRODUCT DESCRIPTION: TR-7 Tar & Mastic Remover clings to and dissolves rubber type mastics, floor tile adhesives, as well as, tar, paint and motor oil stains from masonry and concrete surfaces. TR-7 Tar & Mastic Remover contains water rinseable detergents for easy rinsing. (Will not discolor masonry or concrete surfaces.)

LIMITATIONS: Use only with adequate ventilation. TR-7 Tar & Mastic Remover is a combustible solution and should not be used near any heat source, sparks or open flame. TR-7 Tar & Mastic Remover contains methylene chloride. Wear rubber gloves to protect skin and chemical splash proof goggles. TR-7 Tar & Mastic Remover is more effective when used on exterior surfaces where hot water rinse can be freely applied. The use of high pressure water equipment is recommended for rinsing highly porous masonry. Equipment that will develop 400 to 800 PSI with a water flow of 4-6 gallons per minute offers the highest degree of efficiency.

PRECAUTIONS: Read the entire material safety data sheet and product label for a more thorough evaluation of hazards. Fully protect all adjacent surfaces including, but not limited to painted surfaces, vegetation and aluminum from coming in direct contact with TR-7 Tar & Mastic Remover. Beware of wind drift onto auto and pedestrian traffic.

TECHNICAL DATA: Color/Form: Amber semi paste.

COVERAGE: Approximately 50 sq. ft. per gallon depending on the thickness of the tar or mastic to be removed.

PACKAGING: One, five and fifty-five gallon containers.

INSTALLATION PREPARATORY WORK: To prepare surface, scrape off any heavy accumulation possible

either mechanically or by hand. TR-7 Tar & Mastic Remover is more effective when used on exterior surfaces where water can be freely applied. A test area should be completely processed before beginning overall project to determine precise procedures necessary for most effective removal of tar and mastic and to ensure product is compatible with surface being cleaned. User shall determine the suitability of the product for its intended use and assumes all risk and liability whatsoever in connection therewith. Follow all local, state and/or federal disposal regulations when using this product.

APPLICATION: 1. Using a natural bristled brush or roller, apply a thick heavy coat of full strength TR-7 Tar & Mastic Remover to a dry surface. **DO NOT** apply TR-7 Tar & Mastic Remover with high pressure or airless equipment. 2. While waiting for TR-7 Tar & Mastic Remover to penetrate (5-10 minutes), reapply more on any dry areas. TR-7 Tar & Mastic Remover continues to work as long as product is wet. Allow TR-7 Tar & Mastic Remover to dwell until tar or mastic is completely loosened. 3. Use a wide blade putty knife and scrape off dissolved finish. 4. Re-apply a second coat of TR-7 Tar & Mastic Remover over the same area. Allow to dwell until it penetrates then remove dissolved finish with putty knife. 5. Rinse from the bottom up when conditions permit. For best results, rinse surface with a pressure washer, preferably with hot water. Rinse dissolved residue completely from surface. Failure to do so may result in staining.

AVAILABILITY: Available through a network of distributors and dealers established in cities across the United States and Canada.

NOTICE: The information and recommendations made herein are based on ABRP, Inc., research and the research of others, and are believed to be accurate. However, no guarantee of their accuracy is made because ABRP, Inc., cannot anticipate every possible application of ABRP, Inc., products, nor anticipate every variation encountered in project surfaces, job conditions, and methods used. For this reason, purchasers shall make their own tests to determine the suitability of such products for a particular purpose. Purchasers assume all risk of use, application and handling of products. Statements concerning the possible use of ABRP, Inc., products are not intended as recommendation to use ABRP, Inc., products in the infringement of any patent.

LIMITED WARRANTY: This warranty is valid for one year from the date of product purchase. Purchaser's claims recovery is limited solely to the following warranty from ABRP, Inc., if the product herein is shown to be defective: ABRP, Inc., at its option, will either replace the product or refund the purchase price. Contact ABRP, Inc., to make claim under this warranty. The purchaser must have proof of purchase from the label and the original sales receipt. Proper surface preparation is essential to the product's performance and is a necessary prerequisite for triggering ABRP, Inc.'s obligation under this warranty. Read and follow label directions and observe all safety precautions in the use of this product. ABRP, Inc., further disclaims, and shall not be liable for, incidental, consequential or indirect damage and/or personal injuries including death arising from the use of this product or the cost of labor involved in its application or any reapplication of product that is replaced. **SELLER MAKES NO WARRANTY, EXPRESSED OR IMPLIED, CONCERNING THE USE OF THIS PRODUCT OTHER THAN INDICATED ON THE LABEL. BUYER ASSUMES ALL RISK OF USE AND/OR HANDLING OF THIS MATERIAL WHEN SUCH USE AND/OR HANDLING IS CONTRARY TO LABEL INSTRUCTIONS. NO OTHER WARRANTIES ARE MADE, EXPRESSED OR IMPLIED, INCLUDING WITHOUT LIMITATION WARRANTIES AS TO MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. IN ALL EVENTS, ABRP, INC.'S LIABILITY SHALL BE LIMITED SOLELY TO REPLACEMENT OF THE PRODUCT PROVIDED ABOVE.** This limited warranty may not be modified or extended by manufacturer's representatives, distributors or dealers of ABRP, Inc., products. This warranty gives the purchaser specific legal rights, as well as rights which may vary from state to state. ABRP, Inc. specifically disclaims any and all other obligations or liability to any party relative to the sale, use or application of its products.

TECHNICAL SERVICES: ABRP, Inc., employs in-field technical representatives to answer questions for architects, building owners and contractors.

REFERENCING: Catalog, product specifications, brochures, list of national registered historical landmarks restored with ABRP, Inc., products and video training tapes demonstrating a variety of cleaning and restoration projects being performed with ABRP, Inc. products are available upon request. For more information on many of the specialty building restoration products available to you, please see our website at www.abrp.com or e-mail ABRP, Inc. at abrp@abrp.com.

American Building Restoration Products, Inc. • address: 9720 S. 60th St., Franklin, WI 53132

Corporate office: (414) 421-4125 • Orders ONLY: 1-800-346-7532 • fax: (414) 421-8696 • email: abrp@abrp.com • website: abrp.com

Updated: 7/27/2010 • Copyright © 2010 American Building Restoration Products, Inc.