



LOG-GEVITY™ BIO-STRIP PRODUCT SPECIFICATIONS

PRODUCT NAME

Log-Gevity™ Bio-Strip

MANUFACTURER

American Building Restoration
Products, Inc.
9720 South 60th Street
Franklin, WI 53132
U.S.A.
(414) 421-4125
1-800-346-7532 (Orders Only)
Fax (414) 421-8696
www.abrp.com

PRODUCT DESCRIPTION

Log-Gevity™ Bio-Strip, designed for exterior use, is a multi-purpose stripper, cleaner, refinisher and more. It is formulated to remove a wide variety of coatings from many types of substrates. This product is unique because it is biodegradable, non-flammable, non-acidic, contains no methylene chloride and does not require neutralizing.

Log-Gevity™ Bio-Strip Gel dwells longer providing deeper penetration on multiple layers of paint.

Precautions: Read the entire material safety data sheet and product label for a more thorough evaluation of hazards. Fully protect all adjacent surfaces, as well as floor and general work area, from coming into direct contact with **Log-Gevity™ Bio-Strip**.

Caution: On glass surfaces, all Log-Gevity™ Bio-Strip overspray and/or residue from the stripping process must be immediately removed to avoid adherence to the glass surface.

TECHNICAL DATA

Color/Form: Reddish-brown gel.

Coverage: Bio Strip™ Gel: 50-100 sq. ft. per gallon, depending on layers of paint to strip.

Packaging: One and five gallon containers.

PROPER SURFACE PREPARATION

Prepare a surface free from dirt and oil. It is not necessary to remove loose, peeling or flaking paint. This creates pockets down to the surface which is generally more absorbing than the painted surface.

A test area should be performed prior to beginning overall project to determine optimum dwell time for the product to completely penetrate all layers of the finish.

User shall determine the suitability of the product for its intended use and assumes all risk and liability whatsoever in connection therewith. Follow all local, state, or federal disposal regulations when using the product.

GENERAL DIRECTIONS

1. Using a brush, roller, low pressure (HVLP) sprayer or airless paint sprayer, apply a thick coat of **Log-Gevity™ Bio-Strip** to surface.

Caution: Log-Gevity™ Bio-Strip is slippery when applied to surface. Use extreme caution when working on horizontal surfaces.

2. Allow **Log-Gevity™ Bio-Strip** to remain on the surface until finish has

dissolved. To prevent premature rinsing, wait for the entire surface to become uniformly darkened. This darkened appearance indicates that the **Log-Gevity™ Bio-Strip** has dissolved the underlying finish and is ready to be rinsed.

3. Reapply **Log-Gevity™ Bio-Strip** if necessary.

REMOVAL

1. If possible, scrape all dissolved residue and discard in an appropriate container.

Note: If logs/wood become discolored, leave a solution of **Log-Gevity™ New Log Prep** on the discolored area and allow to dry. Acrytallized residue will appear when the **Log-Gevity™ New Log Prep** dries. Lightly remove crystals from surface without destroying the brightening action of the **Log-Gevity™ New Log Prep** with a very light water rinse.

2. Certain types of log/wood surfaces may have raised grain after stripping is completed. Sanding may be necessary. Sand when surface is dry or brush with stiff bristle brush while surface is wet to smooth out this condition.

CLEAN UP: water flush equipment, shrubbery, sidewalks, blacktop, asphalt, and other adjacent surfaces immediately upon contact. Leave job site free of any trace amounts of **Log-Gevity™ Bio-Strip** or dissolved residue. Never leave behind any containers or equipment. Label appropriate containers of residue for disposal.

STORAGE: All Log-Gevity™ Bio-Strip products should be kept in the containers from which they came.

AVAILABILITY

Available through a network of distributors, dealers and representatives.

NOTICE: The information and recommendations made herein are based on **ABRP, Inc.**, research and the research of others, and are believed to be accurate. However, no guarantee of their accuracy is made because **ABRP, Inc.**, cannot anticipate every possible application of **ABRP, Inc.**, products, nor anticipate every variation encountered in project surfaces, job conditions, and methods used. For this reason, purchasers shall make their own tests to determine the suitability of such products for a particular purpose. Purchasers assume all risk of use, application and handling of products. Statements concerning the possible use of **ABRP, Inc.**, products are not intended as recommendation to use **ABRP, Inc.**, products in the infringement of any patent.

LIMITED WARRANTY

This warranty is valid for one year from the date of purchase. The purchaser of this product shall be entitled to the

following, if the product herein is shown to be defective: **ABRP, Inc.**, at its option, will either replace the product or refund the purchase price. Contact **ABRP, Inc.**, to make claim under this warranty. The purchaser must have proof of purchase from label and original sales receipt. Proper surface preparation is essential to the applicability of this warranty. Read and follow label directions.

ABRP, Inc., shall not be liable for incidental, consequential or indirect damage arising from the use of this product or the cost of labor involved in its application.

Seller makes no warranty, expressed or implied, concerning the use of this product other than indicated on the label. Buyer assumes all risk of use and/or handling of this material when such use and/or handling is contrary to label instructions.

No other warranties are made, expressed or implied, including without limitation warranties as to MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

This limited warranty may not be modified or extended by manufacturer's representatives, distributors or dealers of **ABRP, Inc.**, products.

Some states do not allow the exclusion or limitation of incidental or consequential damages so the above limitation or exclusion may not apply to

the purchaser. This warranty gives the purchaser specific legal rights as well as other rights which may vary from state to state.

TECHNICAL SERVICES

ABRP, Inc., employs in field technical representatives to answer questions for architects, building owners and contractors.

REFERENCING

Catalog, product specifications and brochures are available upon request.

Visit www.Log-Gevity.com for additional information regarding log home restoration and preservation products.

For more information on many of the specialty building restoration products available from ABRP, Inc., please visit www.abrp.com or e-mail ABRP, Inc. at support@abrp.com.

© Copyright 2005 ABR Products, Inc.

