

The user shall determine the suitability of the product for its intended use and assumes all risk and liability whatsoever in connection therewith.

GENERAL DIRECTIONS

- Apply **Log-Gevity™ Citrus Log Stripper Paste** approximately 1/8 - 1/4 inch thick with a trowel or brush.
 - Apply **Log-Gevity™ Citrus Log Stripper Gel** with a natural bristle brush, roller, low pressure (HVLP) sprayer or airless sprayer.
- Allow **Log-Gevity™ Citrus Log Strippers** to remain on the surface until all paint is dissolved. **Log-Gevity™ Citrus Log Strippers** will penetrate an average of one (1) layer of paint every fifteen (15) to thirty (30) minutes.

Note: Product efficiency is slower in cooler temperatures.

Note: **Log-Gevity™ Citrus Log Stripper Paste and Gel** may sag if applied too thick over latex finishes. If sagging occurs, apply thinner coats of **Log-Gevity™ Citrus Log Stripper**. Allow the product to dwell for one (1) hour and apply a second coat directly on top of the first coat.

REMOVAL

- Scrape away the dissolved residue. *Forming a membrane may require leaving **Log-Gevity™ Citrus Log Stripper** on the surface beyond 24 hours depending on the temperature and humidity.* Rinse the surface with a clean sponge or scrub brush and clean water to remove excess **Log-Gevity™ Citrus Log Stripper** residue.

Note: Beware of wind drift onto adjacent surfaces while rinsing or applying **Log-Gevity™ Citrus Log Strippers**.

Note: A soft wire brush may be used to remove dried product missed during rinsing.

- Log-Gevity™ Citrus Log Strippers** do not require neutralization.

STORAGE: **Log-Gevity™ Citrus Log Strippers** should always be stored in the

container in which it was purchased.

DISPOSAL: Contact local, state and/or federal agencies to ensure compliance with regulations governing the disposal of this product along with coatings and finishes that may be removed when using this product.

WARNING: This product contains a chemical known to the State of California to cause cancer, birth defects or other reproductive harm.

AVAILABILITY

Available through a network of distributors, representatives and dealers.

Notice: The information and recommendations made herein are based on ABRP, Inc., research and the research of others and are believed to be accurate. However, no guarantee of their accuracy is made since ABRP, Inc., cannot anticipate every possible application of ABRP, Inc., products, nor anticipate every variation encountered in project surfaces, job conditions and methods used. For this reason, purchasers shall make their own tests to determine the suitability of such products for a particular purpose. Purchasers assume all risk of use, application and handling of products. Statements concerning the possible use of ABRP, Inc., products are not intended as recommendation to use ABRP, Inc., products in the infringement of any patent.

LIMITED WARRANTY

This warranty is valid for one year from the date of purchase. The purchaser of this product shall be entitled to the following, if the product herein is shown to be defective: ABRP, Inc., at its option, will either replace the product or refund the purchase price. Contact ABRP, Inc., to make a claim under this warranty. The purchaser must have proof of purchase from the label and the original receipt. Proper surface preparation is essential to the applicability of this warranty. Read and follow the label directions.

ABRP, Inc., shall not be liable for incidental, consequential, or indirect damage arising

from the use of this product or the cost of labor involved in its application.

Seller makes no warranty, expressed or implied, concerning the use of this product other than indicated on the label. Buyer assumes all risk of use and/or handling of this material when such use and/or handling is contrary to label instructions.

No other warranties are made, expressed, or implied, including without limitation warranties as to **MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE**.

This limited warranty may not be modified or extended by manufacturer's representatives, distributors or dealers of ABRP, Inc., products.

Some states do not allow the exclusion or limitation of incidental or consequential damages so the above limitation or exclusion may not apply to the purchaser. This warranty gives the purchaser specific legal rights, as well as other rights which may vary from state to state.

TECHNICAL SERVICES

ABRP, Inc., employs a manufacturer-direct personal assistance staff and technical representatives to answer questions for architects, building owners and contractors.

REFERENCING

ABRP, Inc., employs in field technical representatives to answer questions for architects, building owners and contractors.

REFERENCING

Catalog, product specifications and brochures are available upon request.

Visit www.Log-Gevity.com for additional information regarding log home restoration and preservation products.

For more information on many of the specialty building restoration products available from ABRP, Inc., please visit www.abrp.com or e-mail ABRP, Inc. at support@abrp.com.



LOG-GEVITY™ CITRUS LOG STRIPPER

PRODUCT NAME(S)

ABR® Citrus Log Stripper- Paste
ABR® Citrus Log Stripper- Gel

MANUFACTURER

American Building Restoration
Products, Inc.
9720 South 60th Street
Franklin, WI 53132
(414) 421-4125
1-800-346-7532 (Orders Only)
Fax (414) 421-8696

PRODUCT DESCRIPTION

Log-Gevity™ Citrus Log Stripper is a unique formula for the removal of failed log finishes. **Log-Gevity™ Citrus Log Stripper** contains no methylene chloride and no neutralizing is needed. The pH balance is non-damaging to logs, future finishes, wood, masonry, plastered walls or metals. It is designed to remove multiple layers of finish, varnish, stains, latex paint and oil paint. It is recommended for log exteriors and interiors. It can also be used on fine furniture and cabinets. **Log-Gevity™ Citrus Log Stripper** remains moist and active longer, thus penetrating more layers in one application.

Note: **Log-Gevity™ Citrus Log Stripper** may damage or soften asphalt, plastic, rubber, tile, linoleum, anodized aluminum and adjacent painted surfaces.

Log-Gevity™ Citrus Log Strippers are ideal for intricate carvings, moldings, pillars, fine furniture and antiques.

When applied uniformly, **Log-Gevity™ Citrus Log Strippers** penetrate multiple layers of paint mil thickness and reduce the water rinse normally needed to dissolve stripper residue. The special paste formula stays wet and active longer than conventional strippers. In some cases, the paste formula may be removed and reused on multiple surfaces of your current stripping project.

Log-Gevity™ Citrus Log Stripper Gel provides a less viscous consistency than the paste formula.

Log-Gevity™ Citrus Log Stripper is ideal for refinishing work and will remove thin layers of varnish, stain and graffiti.

Precautions: Read the entire material safety data sheet and product label for a thorough evaluation of hazards. Fully protect all adjacent surfaces including vegetation from coming in direct contact with **Log-Gevity™ Citrus Log Strippers**. When stripping interiors, lay plastic sheeting on the floor and cover with stacks of newspaper or cardboard to absorb scraped residue.

USE ONLY WITH ADEQUATE VENTILATION!

Close container after each use. Avoid inhalation and use only with adequate ventilation. If using indoors, open all windows and doors and make sure there is fresh air movement. If adequate ventilation cannot be maintained, wear respiratory protection or leave the area. **CAUTION! This product is combustible. Keep away from heat, sparks, flame and all other sources of ignition.**

Eye Protection Required when using **Log-Gevity™ Citrus Log Stripper**. Wear chemical splash proof goggles.

TECHNICAL DATA

Color/Form:
Log-Gevity™ Citrus Log Stripper Paste-putty-colored thick paste.

Log-Gevity™ Citrus Log Stripper Gel-putty-colored gel.

Coverage:

Note: Product may be reusable on some finishes, increasing the amount of coverage per gallon. The amount of coverage may also vary depending on the surface and the layers of finished to be stripped.

Log-Gevity™ Citrus Log Stripper Paste- 25 to 75 square feet per gallon.

Log-Gevity™ Citrus Log Stripper Gel- 75 to 125 square feet per gallon.

Packaging: One and five gallon containers.

PROPER SURFACE PREPARATION

Preparatory Work: Prepare a surface free from dirt and oil.

Prior to beginning the overall project, a test should be performed to determine the optimum dwell time for the product, the number of applications necessary to completely remove all traces of finish from the surface, and if any **Log-Gevity™ Citrus Log Stripper** may be reused for additional application(s).