



LOG-GEVITY™ LOG CHINKING GLIDE PRODUCT SPECIFICATIONS

PRODUCT NAME

Log-Gevity™ Log Chinking GLIDE
Thin and Thick Viscosity

MANUFACTURER

American Building Restoration
Products, Inc.
9720 South 60th Street
Franklin, WI 53132
(414) 421-4125
1-800-346-7532 (Orders Only)
Fax (414) 421-8696
www.abrp.com

PRODUCT DESCRIPTION

Log-Gevity™ Log Chinking GLIDE is a semi-thick water-based lubricant used to create ease in tooling chinking. **Log-Gevity™ Log Chinking GLIDE** keeps chinking from dripping down to lower level logs which is a problem commonly encountered during the tooling process. In order to achieve the aesthetic of exposed sand aggregate, a minimal amount of tooling will still be required immediately following the initial tooling step. By using **Log-Gevity™ Log Chinking GLIDE** (light viscosity), this affect can be easily accomplished. Man hours and clean-up will be reduced dramatically by substituting the standard tooling lubricants with **Log-Gevity™ Log Chinking GLIDE**.

Precautions: Read the entire material safety data sheet and product label for a more thorough evaluation of hazards. Fully protect all adjacent surfaces as well as general work area. When spraying near vegetation, cover plant life with cardboard or other suitable material in case of overspray.

TECHNICAL DATA

Packaging: One and five gallon containers.

Coverage:
150-200 square feet per gallon.

PROPER SURFACE PREPARATION

IF YOU HAVE NEW OR OLD, DIRTY OR WEATHERED LOGS/WOOD

1. Clean logs/wood with **Log-Gevity™ New Log Prep** or **other Log-Gevity™ Product**.
2. Apply a coat of **Log-Gevity™ Log Stain & Stabilizer**.
3. If color is desired, apply color toner with the **Log-Gevity™ Stain & Stabilizer**.
- Note:** Once the **Log-Gevity™ Stain & Stabilizer** is applied, your logs have sufficient protection for 12 months or longer before finish coat or chinking need to be applied.
4. Apply **Log-Gevity™ End Grain Sealer** to exposed log ends.
5. Apply a top coat of **Log-Gevity™ Log Finish Coat**.
6. Apply **Log-Gevity™ Log Chinking** anytime after the stabilizer or finish has been applied and cured.
7. Utilize **Log-Gevity™ Log Chinking GLIDE** during tooling process of log chinking. Apply to tooling apparatus by spraying or dipping.

GENERAL DIRECTIONS

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

Test area should be performed on each

type of surface before overall use of product. Allow test areas to dry thoroughly before determining results. User shall determine the suitability of the product for its intended use and assumes all risk and liability whatsoever in connection therewith.

1. Apply **Log-Gevity™ Log Chinking GLIDE** during tooling process of log chinking.
2. Apply **Log-Gevity™ Log Chinking GLIDE** to tooling apparatus by spraying or dipping.

Follow the complete **Log-Gevity™** product specification sheets for detailed instructions.

DRY TIME: Each wood surface may have different dry times due to wood porosity. Under optimal conditions **Log-Gevity™ Stain & Stabilizer** will flash dry in approximately 30 minutes. Always check wood surfaces prior to usage.

CLEAN UP: Detergent and water.

STORAGE: Keep container closed when not in use. Store in cool place. **This product should be kept out of reach of children and stored away from food.**

DISPOSAL: Do not reuse empty can. Wrap can and place in trash. Leaking or damaged containers should be placed in a plastic bag and discarded. Contact local, state, or federal agencies to ensure compliance of proper disposal methods and respective regulations.

NOTICE: The information and recommendations made herein are based on **ABRP, Inc.**, research and the research of others, and are believed to be accurate.

However, no guarantee of their accuracy is made because **ABRP, Inc.**, cannot anticipate every possible application of **ABRP, Inc.**, products, nor anticipate every variation encountered in project surfaces, job conditions, and methods used. For this reason, purchasers shall make their own tests to determine the suitability of such products for a particular purpose. Purchasers assume all risk of use, application and handling of products. Statements concerning the possible use of **ABRP, Inc.**, products are not intended as recommendation to use **ABRP, Inc.**, products in the infringement of any patent.

LIMITED WARRANTY

This warranty is valid for one year from the date of purchase. The purchaser of this product shall be entitled to the following, if the product herein is shown to be defective: **ABRP, Inc.**, at its option, will either replace the product or refund the purchase price. Contact **ABRP, Inc.**, to make claim under this warranty. The purchaser must have proof of purchase

from label and original sales receipt. Proper surface preparation is essential to the applicability of this warranty. Read and follow label directions.

ABRP, Inc., shall not be liable for incidental, consequential or indirect damage arising from the use of this product or the cost of labor involved in its application.

Seller makes no warranty, expressed or implied, concerning the use of this product other than indicated on the label. Buyer assumes all risk of use and/or handling of this material when such use and/or handling is contrary to label instructions.

No other warranties are made, expressed or implied, including without limitation warranties as to MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

This limited warranty may not be modified or extended by manufacturer's representatives, distributors or dealers of **ABRP, Inc.**, products.

Some states do not allow the exclusion or limitation of incidental or consequential damages so the above limitation or exclusion may not apply to the purchaser.

This warranty gives the purchaser specific legal rights as well as other rights which may vary from state to state.

TECHNICAL SERVICES

ABRP, Inc., employs in field technical representatives to answer questions for architects, building owners and contractors.

REFERENCING

Catalog, product specifications and brochures are available upon request.

Visit **www.Log-Gevity.com** for additional information regarding log home restoration and preservation products.

For more information on many of the specialty building restoration products available from ABRP, Inc., please visit www.abrp.com or e-mail ABRP, Inc. at support@abrp.com.

